


## Type N Slide Lock (TS-12/N)





weatherproofing methods such as tapes and mastics are becoming more and more difficult to install due to the limited amount of space on Remote Radio Units (RRU) and antenna units.

Slide Locks reduce installation time and provide protection from connector degradation and corrosion. They protect jumper to jumper and jumper to antenna/RRU and LMR600 connections. When installed properly our enclosures weather proof to the IP-68 standard.

Gamma PN	AT&T	Cable Size	Connectors
TS-12/N		1/2 Inch Superflex & LMR600 Cables	Type N

Please Note: Slide Locks will not work on compression or field-terminated connections

## Characteristics



- No Tools, Tapes or Mastics Needed for Installation
- Particularly Easy to Install and Reuse Again and Again
- Broad Operating Temperature from -40°C to 90°C
- Installation Temperature -30°C to 60°C
- Protects Against Water Intrusion and Weather Proof Rated to IP68
- May Be Opened and Closed Several Times and Still Protect and Weatherproof Connections
- Designed for Harsh Weather Conditions, UV & OzoneResistance
- Resistant to vibration, temperature fluctuations and moderate impact
- Small foot print makes for easy install for units that have a high quantity of ports. (8-16)



## Type N Slide Lock (TS-12/N)



For best protection and proven results, follow the installation instructions in each slide lock kit. For any questions about the product, feel free to reach out to Gamma Electronics Inc.

Property of Gamma Electronics Inc.
2818 Metropolitan Place, Suite A
Pomona, CA 91767
www.gammaelectronics.net