# 1000SR



Phone: (315) 437-1977 Email: sales@emeraldscreening.com

The Powerscreen® 1000SR is built around the successful 1000 Maxtrak model and features a re-circulating conveyor and a double-deck post-screen to provide a complete crushing and screening process on a single chassis. The machine is designed for direct feed applications without pre-screening on clean rock. At its heart is the Automax® cone crusher which provides excellent reduction and product cubicity for the production of high quality aggregate and sub-base material. Hydraulic release capabilities are designed so that any uncrushable material entering the chamber is safely discharged. Suitable for secondary and tertiary applications, the 1000SR can produce up to three products when oversized material doesn't require re-circulation to the crusher.

## **Features & Benefits**

- Renowned Automax® crusher technology
- Accepts clean all in feed
- Excellent product shape
- High reduction ratio
- Cone feed box level control to maintain choke feeding
- Hydraulic crusher setting
- Cone overload protection
- Heavy duty chassis and track frame
- Metal detector
- Dust suppression system
- Economical to operate with a highly fuel efficient direct drive system
- Patented double deck post screen.
- Suitable for re-circulating oversized material
- Fitted with Powerscreen Pulse Telematics

- Concaves: extra coarse medium coarse, coarse, Autosand®
- Short throw eccentric
- Feed hopper extension plates
- Product conveyor belt weigher
- Electric refuelling pump
- Hydraulic water pump
- Radio remote control
- Urea refuelling pump
- Additional stockpiling conveyor for mid-grade product

- Blasted rock


- Processed ores
- Processed minerals

- Sand & gravel
- River rock
- C & D waste
- Foundry waste

| 1000011          |                      |
|------------------|----------------------|
| Weight (Est)     | 39,640kg (87,391lbs) |
| Transport width  | 3.1m (10'2")         |
| Transport length | 16.9m (55'5")        |
| Transport height | 3.45m (11'4")        |
| Working width    | 3.1m (10'2")         |
| Working length   | 16.9m (55'5")        |
| Working height   | 4.85m (15'11")       |
|                  |                      |



Engines are available that are certified to US EPA and EU off road diesel emission standards. Talk to your dealer about possible certification options (i.e. Tier 3/Stage 3A:, Tier 4i/Stage 3B:, Tier 4F / Stage 4).



Fuel tank capacity: 650 L (171 US Gal)

