

Hardwood+ Tasmanian Oak

Engineered Australian timber species offers the very best of timber flooring, with a cleaner Australian timber aesthetic featuring the subtle grains of Victorian Ash. Our Tasmanian Oak Engineered timber is the latest addition to our Australian species range, displaying the full sprectrum of this tree's distinctive beauty.

12 Layers of UV Acrylic Coating

3mm Veneer of Victorian Ash timber

11mm Engineered Multiply Substrate

Revolutionary 5G locking system

PRODUCT SPECIFICATIONS

Туре	Australian Species Victorian Ash Timber	Board Dimensions	1820/2100 x 170 x 14mm
Description	Engineered multi-layer natural Victorian Ash timber veneer interlocking floor boards featuring G5 Locking System		
Installation Method	Direct Stick or Floating	Profile	Micro-Bevel
Coating	Factory Coated with Twelve Layers of UV Cured Acrylic	Finish	Matte Smooth
Nested Lengths	Max 25% Per Pack	Timber Grading	Standard & Better

PACK SPECIFICATIONS

M² Per Pack	1.85m ² /2.14m ²	Boards Per Pack	6
Pack Dimensions	1850/2130 x 162 x 121mm	Pack Weight	23kg

TEST DATA & WARRANTY

Fire Rating	Critical Heat Flux: 4.2kW/m² Smoke Value: 8% minute	Slip Resistance	Р3
Acoustic Rating	58 LnTw*	warranty	25 Year Residential Warranty 10 Year Commercial Warranty

Timber is a natural material and variations in colour, texture and other naturally occurring features occur between pieces and batches of the same species. Timber flooring, whilst dried during production, continues to take up and give up moisture during its life, depending on weather, aspect and local conditions. In so doing, some movement and changes to the surface of your floor are to be expected and will be apparent. This is normal and may include fine cracks on and between boards and changes in colour. Access complete warranty information at embelton.com

