# EMBELTON

### embelton.com



## European Oak Timber Hybrid

Timber Hybrid is a groundbreaking range, offering affordable flooring that possesses the look and feel of real European Oak and Australian species while utilising a hybrid core for extra durability. Experience the timeless beauty of timber flooring with the added benefits of a hybrid board. With a 5Gi locking system installation is a breeze. 7 Layers of UV Acrylic Coating

1.2mm Solid European Oak Timber Veneer

Stone Polymer Composite Core

Revolutionary 5Gi Locking System

1.5mm Acoustic Foam Underlay

Туре	Timber Hybrid	Board Dimensions	1830 x 190 x 7.5mm
Description	Stone Polymer Composite flooring featuring Valinge 5Gi Locking System	Profile	Micro-Bevel
Installation Method	Floating	Finish	Light Wire Brush, Matte Finish
Coating	Factory Coated with Seven Layers of UV Cured Acrylic	Timber Veneer	1.2mm
Timber Grade	ABCD	Nested Lengths	Max 40% Per Pack
Underlay	1.5mm High Density Closed Cell Acoustic Foam Attached		

### PACK SPECIFICATIONS

M <sup>2</sup> Per Pack / Pallet	2.08m <sup>2</sup> /146.03m <sup>2</sup>	Boards Per Pack	6
Pack Weight	24.5kg		

#### TEST DATA & WARRANTY

Fire Rating	Critical Heat Flux: 5.1 kW/m2 Smoke Value: 38 %.min	Slip Resistance	P3
Respirable Crystaliine Silica	Not Detected	Sustainability	Forestry Stewardship Certification® (FSC®) & Best Environmental Practice
Warranty	25 Year Residential Warranty   10 Year Commercial Warranty		

Timber is a natural material and variations in colour, texture and other naturally occurring features occur between pieces and batches of the same species. Timber flooring, whilst dried during production, continues to take up and give up moisture during its life, depending on weather, aspect and local conditions. In so doing, some movement and changes to the surface of your floor are to be expected and will be apparent. This is normal and may include fine cracks on and between boards and changes in colour. Access complete warranty information at <u>embelton.com</u>



The mark of responsible forestry FSC® C132800