

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 01.09.2021

Version number 2003

Revision: 01.09.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **ATTBLIME - AB6**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites  
 Product category PC9a Coatings and paints, thinners, paint removers  
 Process category PROC5 Mixing or blending in batch processes  
 Environmental release category ERC2 Formulation into mixture  
 Application of the substance / the mixture Flattening agent, Matting agent

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: DM Metrology Inc.  
 14-1860 Appleby Line, Suite 216  
 Burlington, ON L7L 6M6  
 Tel +1 905 691 1116  
 sales@dmmetrology.com  
 Manufacturer Graichen Produktions- und Vertriebs- GmbH  
 Darmstädterstraße 127-129  
 D-64625 Bensheim  
 Germany  
 Tel.: +49 6251 7707880  
 Fax: +49 6251 77901  
 E-Mail: ehs@graichen-bensheim.de  
 www.graichen.net

Further information obtainable from: Environment protection department

#### 1.4 Emergency telephone number:

During office hours: +49(0)6251/73103  
 Out of office hours: +49(0)172/7478476

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008  
 Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07

Signal word: Danger

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
 H319 Causes serious eye irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P264 Wash thoroughly after handling.  
 P280 Wear eye protection / face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337+P313 If eye irritation persists: Get medical advice/attention.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

#### 2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

CAS: 294-62-2 | Cyclododecan

vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### 3.2 Chemical characterisation: Mixtures

Description: Active substance with propellant

Dangerous components:

CAS: 106-97-8	butane (containing ≤ 0,1 % butadiene (106-99-0))	25 – 50%
EINECS: 203-448-7	⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
CAS: 74-98-6	propane	10 – 25%
EINECS: 200-827-9	⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 01.09.2021

Version number 2003

Revision: 01.09.2021

**Trade name: ATTBLIME - AB6**

		(Contd. of page 1)
CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10 – 25%
CAS: 294-62-2 EINECS: 206-033-9	Cyclododecan non-classified PBT substance	2.5 – 10%
CAS: 287-92-3 EINECS: 206-016-6	cyclopentane ⚠ Flam. Liq. 2, H225; Aquatic Chronic 3, H412	2.5 – 10%
CAS: 291-64-5 EINECS: 206-030-2	cycloheptane ⚠ Flam. Liq. 2, H225	2.5 – 10%
CAS: 75-28-5 EINECS: 200-857-2	isobutane (containing ≤ 0,1 % butadiene (106-99-0)) ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 2.5%

. Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### . 4.1 Description of first aid measures

- . After inhalation: Supply fresh air; consult doctor in case of complaints.
- . After skin contact: Wash with water and soap and rinse thoroughly
- . After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- . After swallowing: Seek immediate medical advice.

#### . 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### . 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### . 5.1 Extinguishing media

- . Suitable extinguishing agents: CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### . For safety reasons unsuitable extinguishing agents:

Water in the full ray

#### . 5.2 Special hazards arising from the substance or mixture

Carbondioxid (CO<sub>2</sub>)

#### . 5.3 Advice for firefighters

##### . Protective equipment:

Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.

### SECTION 6: Accidental release measures

#### . 6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.  
Ensure adequate ventilation  
Keep away from ignition sources.

#### . 6.2 Environmental precautions:

Keep contaminated washing water and dispose of appropriately.  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.

#### . 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

#### . 6.4 Reference to other sections

See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

#### . 7.1 Precautions for safe handling

##### . Information about fire - and explosion protection:

Open and handle receptacle with care.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.  
Do not spray onto a naked flame or any incandescent material.

#### . 7.2 Conditions for safe storage, including any incompatibilities

##### . Requirements to be met by storerooms and receptacles:

Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.

##### . Information about storage in one common storage facility:

Store away from oxidising agents.

##### . Further information about storage conditions:

Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

(Contd. on page 3)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 01.09.2021

Version number 2003

Revision: 01.09.2021

**Trade name: ATTBLIME - AB6**

. 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 2)

### SECTION 8: Exposure controls/personal protection

## . 8.1 Control parameters

. Additional information about design of technical facilities: No further data; see item 7.

. Ingredients with limit values that require monitoring at the workplace:

**CAS: 106-97-8 butane (containing ≤ 0,1 % butadiene (106-99-0))**

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

**CAS: 67-63-0 propan-2-ol**

WEL	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm Long-term value: 999 mg/m <sup>3</sup> , 400 ppm
-----	--

. DNELs

**CAS: 67-63-0 propan-2-ol**

Oral	DNEL Long-term - systemic effects	26 mg/kg bw/day (general (Allgemeinbevölkerung))
Dermal	DNEL Long-term - systemic effects	319 mg/kg bw/day (general (Allgemeinbevölkerung)) 888 mg/kg bw/day (Workers (Arbeitnehmer))
	DNEL Long-term - systemic effects	89 mg/m <sup>3</sup> (general (Allgemeinbevölkerung)) 500 mg/m <sup>3</sup> (employee / Arbeitnehmer) 500 mg/m <sup>3</sup> (Workers (Arbeitnehmer))

. PNECs

**CAS: 67-63-0 propan-2-ol**

PNEC Soil (Boden)	28 mg/kg
PNEC fresh water sediment (Süßwassersediment)	552 mg/kg
PNEC fresh water (Süßwasser)	140.9 mg/l
PNEC marine water sediment	552 mg/kg
PNEC Marine water	140.9 mg/l
PNEC-STP	2,251 mg/l

. Additional information: The lists valid during the making were used as basis.

## . 8.2 Exposure controls

. Personal protective equipment:  
. General protective and hygienic measures:  
. Respiratory protection:  
. Protection of hands:

Wash hands before breaks and at the end of work.

Not required.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

. Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

. Penetration time of glove material

Value for the permeation: Level ≤ 0,7 mm 480min (8h) EN374

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

. Eye protection:

Tightly sealed goggles

. Body protection:

Protective work clothing

### SECTION 9: Physical and chemical properties

## . 9.1 Information on basic physical and chemical properties

. General Information

. Appearance:

Form:	Aerosol
Colour:	Whitish
Odour:	Characteristic
Odour threshold:	Not determined.

. pH-value at 20 °C: 6.75

. Change in condition

Initial boiling point and boiling range: -44.5 °C

. Flash point: -97 °C

. Flammability (solid, gas): Not applicable.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 01.09.2021

Version number 2003

Revision: 01.09.2021

**Trade name: ATTBLIME - AB6**

(Contd. of page 3)

. Ignition temperature:	230 °C
. Decomposition temperature:	Not determined.
. Auto-ignition temperature:	Product is not selfigniting.
. Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
. Explosion limits:	
Lower:	1.5 Vol %
Upper:	12 Vol %
. Vapour pressure at 20 °C:	8,300 hPa
. Density at 20 °C:	0.672 g/cm <sup>3</sup>
. Relative density	Not determined.
. Vapour density	Not determined.
. Evaporation rate	Not applicable.
. Solubility in / Miscibility with water:	Fully miscible.
. Partition coefficient: n-octanol/water:	Not determined.
. Viscosity:	
Dynamic:	Not determined.
. Solvent content:	
Organic solvents:	86.6 %
VOC (EC)	591.4 g/l
VOC (EU) (%)	88.0 %
Solids content:	8.0 %
. <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- . **10.1 Reactivity** No further relevant information available.
- . **10.2 Chemical stability**
- . Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- . **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- . **10.4 Conditions to avoid** No further relevant information available.
- . **10.5 Incompatible materials:** No further relevant information available.
- . **10.6 Hazardous decomposition products:** Hazardous thermal decomposition products may include: Formaldehyde, Carbon dioxide, Carbon monoxide, Methanol

### SECTION 11: Toxicological information

- . **11.1 Information on toxicological effects**
- . Acute toxicity Based on available data, the classification criteria are not met.

. LD/LC50 values relevant for classification:

#### CAS: 67-63-0 propan-2-ol

Oral	LD50	5,840 mg/kg (rat) (Acute Oral Toxicity)
Dermal	LD50	12,870 mg/kg (rab) (Acute Dermal Toxicity)
Inhalative	LC50/4h	72.6 mg/l (rat)
	LC50/6h	> 25 mg/l (rat) (Acute Inhalation Toxicity)

. Primary irritant effect:

. Skin corrosion/irritation

#### CAS: 67-63-0 propan-2-ol

Ätz-/Reizwirkung auf die Haut (4h) | (rabbit) (Acute Dermal Irritation/Corrosion)

. Serious eye damage/irritation

#### CAS: 67-63-0 propan-2-ol

Schwere Augenschädigung/-reizung | (rabbit) (Acute Eye Irritation/Corrosion)

. Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

. Additional toxicological information:

#### CAS: 67-63-0 propan-2-ol

NOAEL, maternal	400 mg/kg KG/day (rat)
NOAEL, parents	500 mg/kg KG/day (Two-Generation Reproduction Toxicity)
	853 mg/kg KG/day (rat) (One-Generation Reproduction Toxicity Study)

. CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

. Germ cell mutagenicity Based on available data, the classification criteria are not met.

. Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 01.09.2021

Version number 2003

Revision: 01.09.2021

**Trade name: ATTBLIME - AB6**

(Contd. of page 4)

. Reproductive toxicity

**CAS: 67-63-0 propan-2-ol**

Oral NOAEL, Parents | 500 mg/kg (rat) (Two-Generation Reproduction Toxicity)

. STOT-single exposure Based on available data, the classification criteria are not met.

. STOT-repeated exposure

**CAS: 67-63-0 propan-2-ol**

STOT RE | mg/kg/day (rat)

. Aspiration hazard Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information****12.1 Toxicity**

. Aquatic toxicity:

**CAS: 106-97-8 butane (containing ≤ 0,1 % butadiene (106-99-0))**

EC50 (96h) | 7.71 mg/l (Algae)

LC50 (96h) | 27.98 mg/l (Fisch)

**CAS: 74-98-6 propane**

EC50 (96h) | 7.71 mg/l (Algae)

LC50 (96h) | 27.98 mg/l (Fisch)

**CAS: 67-63-0 propan-2-ol**

EC50 | &gt; 100 mg/l (Bacteria)

EC50 (48h) | &gt; 100 mg/l (daphnia magna/gr. Wasserfloh)

EC50 (72h) | &gt; 100 mg/l (Scenedesmus subspicatus)

EC50 (96h) | &gt; 1,000 mg/l (Scenedesmus subspicatus) (Freshwater Alga and Cyanobacteria, Growth Inhibiti)

LC50 (24h) | 9,714 mg/l (daphnia magna/gr. Wasserfloh) (Daphnia sp. Acute Immobilisation Test)

9,640 mg/l (Pimephales promelas (fettköpf. Ellritze)) (Fish, Acute Toxicity Test)

LC50 (48h) | &gt; 100 mg/l (Leuciscus idus (Goldorfe))

LC50 (96h) | &gt; 9,640 – 10,000 mg/l (Pimephales promelas (fettköpf. Ellritze)) (Fish, Acute Toxicity Test)

LOEC (8d) | 1,000 mg/l (Algae)

EC50 (3h) | &gt; 1,000 mg/l (activated sludge) (Mikroorganismen/Wirkung auf Belebtschlamm)

NOEC (21d) | 30 mg/l (daphnia magna/gr. Wasserfloh) (Daphnia magna Reproduction Test)

NOEC (96h) | 1,000 mg/l (Scenedesmus subspicatus) (Freshwater Alga and Cyanobacteria, Growth Inhibiti)

**CAS: 75-28-5 isobutane (containing ≤ 0,1 % butadiene (106-99-0))**

EC50 (96h) | 7.71 mg/l (Algae)

LC50 (96h) | 27.98 mg/l (Fisch)

**12.2 Persistence and degradability****CAS: 67-63-0 propan-2-ol**

Biodegradability 30d | 70 – 84 % (aerob) ((Derterm. of the "Ready" Biodegr. Closed Bottle))

**12.3 Bioaccumulative potential****CAS: 67-63-0 propan-2-ol**

Log Pow | 0.05

**12.4 Mobility in soil**

No further relevant information available.

. Additional ecological information:

. General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**12.5 Results of PBT and vPvB assessment**

. PBT:

CAS: 294-62-2 | Cyclododecan

. vPvB:

Not applicable.

**12.6 Other adverse effects**

No further relevant information available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

. Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

. European waste catalogue

HP3 | Flammable

. Uncleaned packaging:

. Recommendation:

Disposal must be made according to official regulations.

. Recommended cleansing agents:

Water, if necessary together with cleansing agents.

(Contd. on page 6)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 01.09.2021



Version number 2003

Revision: 01.09.2021

Trade name: ATTBLIME - AB6

(Contd. of page 5)

### SECTION 14: Transport information

. 14.1 UN-Number . ADR, IMDG, IATA	UN1950
. 14.2 UN proper shipping name . ADR . IMDG . IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
. 14.3 Transport hazard class(es) . ADR	
. Class . Label	
. IMDG, IATA	
. Class . Label	
. 14.4 Packing group . ADR, IMDG, IATA	Void
. 14.5 Environmental hazards:	Not applicable.
. 14.6 Special precautions for user . Hazard identification number (Kemler code): . EMS Number: . Stowage Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
. Segregation Code	
. 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
. Transport/Additional information:	
. ADR . Limited quantities (LQ) . Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
. Transport category . Tunnel restriction code	2 D
. IMDG . Limited quantities (LQ) . Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
. UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

. 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
. Directive 2012/18/EU	
. Named dangerous substances - ANNEX I	None of the ingredients is listed.
. Seveso category	P3a FLAMMABLE AEROSOLS
. Qualifying quantity (tonnes) for the application of lower-tier requirements	150 t
. Qualifying quantity (tonnes) for the application of upper-tier requirements	500 t

(Contd. on page 7)

GB

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 01.09.2021

Version number 2003

Revision: 01.09.2021

**Trade name: ATTBLIME - AB6**

(Contd. of page 6)

**15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. Department issuing SDS:

Environment protection department.

. Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

. \* Data compared to the previous version altered.

GB