KAIA

LIN

INSTALLATION MANUAL



₩ 125 mm

300 mm

Stem Length

Stem Colour

Ceiling Rose

Weight Certification

EU/UK

Lamps

Solid brass Indoors 300 x 125 mm 1500 mm Polished nickel 0.4 kg IP20 CE 230 V Ø 80 x 25 mm; flat Ø 100 max. 60 W, S14d, our suggestion: 3,1 W, 3x linear opal LED, 2700 K, Mains (Phase) dimmable* EPREL ID 566201, 52290

INSTALLATION

Before commencing installation ensure the relevant mains supply has been safely isolated/disconnected. Installation should be carried out by a qualified electrician. Ensure all electrical connections are tight with no loose strands, including factory made connections.

- 1. Remove the base from the installation bracket.
- 2. Affix the bracket to the ceiling with 2 screws (hole size max. 4.5 mm, 50 mm apart).
- 3. Connect the unit to the mains.
- 4. Fix the unit back on its base and retighten 2 screws on the side.

STEP 1 TOP VIEW

STEP 2 SIDE VIEW













LAMP INSTALLATION

- Before commencing installation ensure the relevant mains supply has been switched off.
- Use supplied fabric gloves to prevent any stains on the surface of the lamp.
- Due to risk of glass fracture handle the lamp with care!
- Whilst applying pressure push the socket into the lamp holder in the marked place. Remove the lamp from the lamp holder carefully with both hands.

CARE INSTRUCTION

- 1. Use a soft dry cloth to ensure a fingerprint free surface. We recommend the use of micro fibre cloths.
- 2. Warning: do not use alcohol or other solvents for cleaning.

* On very rare occasions, these lamps may appear to have a slight buzzing or flickering. As is the case with all retro LED lamps, this is likey casued by a number of outside influences such as incorrect installation, wiring, dimming or transformers and in some instances low electrical resistance.

** Please contact sales@kaiaeditions.com for further information on dimmers etc. Please note KAIA Ltd cannot take any responsibility for the connection with your dimming or central control system. It is the customer's responsibility to ensure the compatibility with their systems.

