



XtremeSavE SPLIT












Cooling/Heating





Energy Saving -----

High-efficiency Fan Blade and Ducts













- 3D Airflow







Powerful Cooling

Midea inverter air conditioners offer three operating power



ThermoStatic Technology

Keeping you steadily cool within ± 0.5 °C Thanks to the precise control of the Inverter Quattro" 's



Inverter Quattro" AC

Dual Filtration

The Dual Filtration system thoroughly eliminates

STEP1: High Density Pre Filter









Midea Air Conditioner

App-based Remote Based on the cloud service under M-Smart Security

Discover the MideaAIR to get your home life connect Google Play







	Net dimension (mn)		
	Packing dimension (mm)		
	Hert/Snoss weight, (kg)		
	Indoor noise level (HBIA)(ETurbe, HB, TM) Les		
Control	Outdoor		
Control	Net dimension (mno		
Protocol, the MideoA/R app makes with versatile functions just in hand.	Packing dimension (Inno		
ted	Services weight (NO) FREME Street Street Services model with Georgiahit model to at Highly-efficient indox Feature		
	Smart Sleep Curve		
Set the most appropriate			
Set the most appropriate temperature curve for you and your lensity members. There're default	Gast Stritt		

Capacity (Ma/h)	Cooling	TH2000 (5500-16000)	THR00 (5200-21000)	T122000 (\$400-20000)	112790068400-82000
		T\$10600	73/6900	T3:8500	1523290
	Heating	3550 (7055-6835)	5350 (563-656)	7690 (X356-6232)	830002521-96723
Framer Inguit (M)	Cooling	T1896 (360-1600)	T11020 (400-NBO)	TING (479-2400)	712900(60-2900)
		13 1096	133604	78.0050	19,2605
	Hosting	972 (260-150)	1608 (420-2000)	206 (679-3000)	2000790-5000
BER ONLOG/W		TH55.4	TU3.4	T113-65	TITLES
		T3.649	7202	7393	116.0
00P (NeW)		168	100	350	195
Rated Current (K)	Cooling	T1435	115.86	1033	71936
		135	T3.7.45	T2804	137.74
	Hosting	6.68	630	9.74	9.60
Power supply 079,76743		1/280/80(18)	9290/60(5E)	1290/80(50)	1/250/68(50)
Indoor air flour (m ¹ /h) (*bulbo,14,145/La)		685,405,485/300	1250,790,590,990	1250,750,700,910	1420/1300/110/980
Pathiperant.		RettA	DEGA	HEEA.	REGA
Metrigenent pipe	Uniquist state Okumenterimental	635	636	932	102
	Ges side Otanssiav (men)	11.7	0.7	15.0	.19
Application area (11°):		10-21	24:35	20-43	38-63
Induce					
Net dinember (mm)	WIDH	800/884287	1000+220+335	1080x236x335	1359+292+562
Packing dimension (mm)	WIEH	87542854375	195425646	TSSnZSndS	1540+450+380
Herl/Sinces weight, (kg)		8.010	18.6/10	38.6/39.4	2075.9
Indoor noise level 0/86A/QETurini/Hi/Hi/Les		41.542/3332/3	55/49/32/4/32	10/35/93/4/27	555098/41/38
Outdoor					
Net dimension (mno	WOH	800v555v554	845+565+702	\$46,480,680	\$46,400,000
Packing dimension (mm)	WITH	920×390×675	965×395×365	1090+500+875	1090+500+665
Hely/Ences weight (kg)		373/969	48.404.6	198/954	843/983

























