

BBK PERFORMANCE LLC
3060 Performance Circle
Deland, FL 32724

For any questions, email us:
TECH@BBKPERFORMANCE.COM



INSTALLATION INSTRUCTIONS - INS088

TUNED LENGTH SHORTY HEADER

Part # 1615 and 16150 // 1996 - 2004 Ford Mustang 4.6L 2-V



SPECIAL TOOLS REQUIRED: No special tools required.



INSTALL TIME: Approximately 3-4 hours.



DIFFICULTY: Average.



After 500 miles of drive, check the header bolts and re-tighten.

MADE IN U.S.A.

IMPORTANT: All appropriate safety equipment and gear must be used during the installation of this or any BBK Performance products or any time you work on a vehicle. BBK Performance accepts no responsibility for injuries or damage caused by or during the installation of this product.

UPDATED LAST: March 2019



FOLLOW THESE INSTRUCTIONS CAREFULLY TO ENSURE CORRECT FITMENT AND OPERATION

STEP 1

Disconnect the negative battery terminal, remove the intake hose and air box, and remove the strut tower brace if applicable.

STEP 2

Lift the vehicle as high as possible with a jack and support with jack stands.

STEP 3

Unplug all oxygen sensors. (Removal from the H-Pipe is not necessary)

STEP 4

Unbolt the H-Pipe from the exhaust manifolds and cat-back system and remove. Remove the motor mount to K member nuts.

STEP 5

Carefully jack up the engine (We recommend using a solid block of wood to place under the engine) until the mounts rise out of the K member.

NOTE!!! Watch for any hang-ups such as wiring harnesses or hoses while lifting engine. Safely support in this position.

DRIVER SIDE

STEP 6

Disconnect the EGR by-pass tube from the top of the exhaust.

STEP 7

Remove the bolt from the steering shaft at the steering rack, and move the shaft to the side.

NOTE!!! Although not necessary, you may find more working space by removing the motor mounts from the engine block.

STEP 8

Remove the stock exhaust manifold and gasket.

NOTE!!! On some vehicles it may be easier to access the upper exhaust manifold bolts from above the engine.

STEP 9

Install the BBK Header and supplied gasket. These headers have slotted mounting holes which will allow you to start some of the header bolts before placement.

NOTE!!! On some applications it may be easier to re-use some of the original stud type header bolts.

STEP 10

Insert one collector bolt down through each of the slotted holes in the collector flange.

STEP 11

Re-install any EGR or AIR fittings if applicable, Re-install motor mount and reassemble the steering shaft.

NOTE!!! Be sure to use supplied anti seize on any metal threaded tube fittings.

 **MADE IN U.S.A.** 

IMPORTANT: All appropriate safety equipment and gear must be used during the installation of this or any BBK Performance products or any time you work on a vehicle. BBK Performance accepts no responsibility for injuries or damage caused by or during the installation of this product.

UPDATED LAST: March 2019



FOLLOW THESE INSTRUCTIONS CAREFULLY TO ENSURE CORRECT FITMENT AND OPERATION

PASSENGER SIDE

STEP 12

Unbolt and remove starter from the bell housing. NOTE!!! Remove the motor mount from the block if needed.

STEP 13

Remove stock exhaust manifold and gasket.

STEP 14

Install BBK Header and supplied gasket.

STEP 15

Insert supplied collector studs.

STEP 16

Re-install the motor mount and starter.

STEP 17

Lower the engine into the chassis and tighten the nuts.

NOTE!!! Be sure to check if the engine is sitting all the way down and even on the motor mounts before tightening.

STEP 18

Re-install the H-Pipe using the supplied hardware. Plug in all the oxygen sensors.

STEP 19

Lower the vehicle and re-install the intake hose and strut tower brace (if applicable). Reconnect the negative battery terminal.

STEP 20

Start vehicle and listen for leaks.

 MADE IN U.S.A. 

IMPORTANT: All appropriate safety equipment and gear must be used during the installation of this or any BBK Performance products or any time you work on a vehicle. BBK Performance accepts no responsibility for injuries or damage caused by or during the installation of this product.

UPDATED LAST: March 2019

BBK PERFORMANCE LLC
3060 Performance Circle
Deland, FL 32724

For any questions, email us:
TECH@BBKPERFORMANCE.COM



FOLLOW THESE INSTRUCTIONS CAREFULLY TO ENSURE CORRECT FITMENT AND OPERATION


IMPORTANT NOTICE!

FOR ALL 1996 - 2004 MUSTANG 4.6L 2&4 V HEADERS

BBK has intentionally crimped the driver side header tube(s) in this set to provide necessary clearance for the steering shaft.

BBK has performed extensive R&D / dyno testing on this design.
The crimp does not have a negative effect on performance, tuning, or exhaust flow output.

THE CRIMP DOES NOT CONSTITUTE A WARRANTY CLAIM.



MADE IN U.S.A.

IMPORTANT: All appropriate safety equipment and gear must be used during the installation of this or any BBK Performance products or any time you work on a vehicle. BBK Performance accepts no responsibility for injuries or damage caused by or during the installation of this product.

UPDATED LAST: March 2019