

INSTALLATION INSTRUCTIONS - INS013

1986 - 2004 MUSTANG GT

THROTTLE BODY POSITION SENSOR

Part #1684 and 1685



SPECIAL TOOLS REQUIRED: Volt Meter



INSTALL TIME: Approximately 30 minutes



DIFFICULTY: Very easy



MADE IN U.S.A.

IMPORTANT: All appropriate safety equipment and gear must be used during the installation of this or any BBK Performance products or any time you work on a vehicle. BBK Performance accepts no responsibility for injuries or damage caused by or during the installation of this product.

UPDATED LAST: March 2019



FOLLOW THESE INSTRUCTIONS CAREFULLY TO ENSURE CORRECT FITMENT AND OPERATION

STEP 1

With the engine cool to avoid burns and the negative battery cable disconnected to avoid shock, unplug the throttle position sensor from the harness.

STEP 2

Using a Phillips screwdriver, remove the two screws which attach to the sensor to the factory throttle body.

STEP 3

When installing the new TPS keep in mind that the sensor is spring-loaded – therefore, it must be installed counter clockwise to its lined up position then rotate the sensor clockwise and install the two Phillips head screws.

STEP 4

After reconnecting the sensor to the harness and reattaching the negative battery cable – now turn the key to the "on" position (not running) and using a voltmeter check the voltage reading off the middle wire of the sensor to insure approximately .8-1.0 volt. To change voltages simply loosen the two Phillips head screws and rotate the sensor to change voltage.

 **MADE IN U.S.A.** 

IMPORTANT: All appropriate safety equipment and gear must be used during the installation of this or any BBK Performance products or any time you work on a vehicle. BBK Performance accepts no responsibility for injuries or damage caused by or during the installation of this product.

UPDATED LAST: March 2019