



# PRATICA

Professionale / *Professional*

- TRADIZIONALE DESIGN ITALIANO, QUALITÀ DI MACINATURA COSTANTE – ON DEMAND
- TRADITIONAL ITALIAN DESIGN, CONSISTENT GRINDING QUALITY - ON-DEMAND

## DATI TECNICI / TECHNICAL DATA

Diametro macine	Grinding disc diameter	65 Ø mm
Materiale macine	Grinding disc material	Acciaio temperato Hardened steel
Tensione / Frequenza / Fase	Voltage / Frequency / Phase	100 V / 50 Hz / 1 100 V / 60 Hz / 1 110 - 127 V / 60 Hz / 1 220 - 240 V / 50 Hz / 1 220 - 240 V / 60 Hz / 1
Watt	Watt	220 - 240 V drive: 440 W 100 V drive: 510 W 110 -127 V drive: 580 W
Giri motore	RPM	1400 rpm (50 Hz) 1650 rpm (60 Hz)
Capacità macinazione	Grinding capacity	50 Hz: 2.0 Sec 60 Hz: 1.7 Sec
Capacità tramoggia	Hopper capacity	1,2 kg
Dimensioni (L x A x P)	Dimensions (w x h x d)	195 x 583 x 283 mm
Peso netto	Net weight	11,2 kg
Peso di trasporto	Shipping weight	12,7 kg

Opzioni colore / Color options



## CERTIFICAZIONI / LISTINGS / CERTIFICATIONS

CE, (CB), ETL Safety, ETL Sanitation,  
Conforms to:

- EC/EN 60335-1 except IPX1
- IEC/EN 60335-2-64 except IPX1

Certified to:

- Standard ANSI/UL 763
- CSA C22.2 No. 195
- NSF / ANSI 8

*Voltaggi speciali a richiesta / Other elec. specifications available on request*



## ANFIM S.r.l.

20141 Milano Italy  
Via B. Verro, 33/5

Tel. (+39) 02 8465054 | Fax (+39) 02 8464401  
info@anfim.it | www.anfim.it

COMPANY OF THE **HEMRO**  
GROUP

Global Coffee Grinding Solutions