

A close-up photograph of a person wearing a grey hoodie and black work gloves. The person is using a red and black AC Delco power tool, likely a ratchet or impact driver, to work on a metal component of a vehicle. The tool has the AC Delco logo on its side. The background is slightly blurred, showing the person's torso and the car's body panels.

ACDelco

acdelco-tools.com

Auto & Equipment Tools

G12 SERIES

12V BATTERY PLATFORM

Ever Growing Family

Ratchet Wrench
Impact Wrench
Impact Driver
Polisher
& more...

Brushless
Compact
Variable Speed
Powerful Torque
Versatile Application



Sign up newsletter to receive G12 battery discount

| www.acdelco-tools.com

ACDelco

Distributed by Durofix Inc

909-980-3323

info@durofix.com

9168 Pittsburgh Ave, Rancho Cucamonga, CA 91730

www.acdelco-tools.com

shop.durofix.com



G12 SERIES

- Compact & ergonomic design
- 12 Li-ion platform
- Ideal for extensive tools portfolio
- One battery for all

ACDelco



Cordless Ratchet Wrench



		BRUSHLESS			BRUSHLESS		BRUSHLESS
Model#	ARW1207	ARW1210-2	ARW1209	ARW1208	ARW1210-3	ARW1218-3	ARW1210-4
Drive Size	1/4"	1/4"	3/8"	3/8"	3/8"	3/8"	1/2"
Max. Torque	30 ft-lbs	45 ft-lbs	45 ft-lbs	55 ft-lbs	65 ft-lbs	40 ft-lbs	70 ft-lbs
No Load Speed	240 RPM	0-240 RPM	170 RPM	0-170 RPM	0-220 RPM	250 RPM	0-220 RPM

3/8" Impact Wrench



ARI12104

Drive Size
3.8" square

Max. Torque
90 ft-lbs / 120 Nm

No Load Speed
0-3100 RPM

3/8" Impact Driver



ARI12105

Drive Size
1/4" hex shank

Max. Torque
82 ft-lbs / 110 Nm

No Load Speed
0-3100 RPM

3/8" 2-speed Drill / Driver



ARD12119

Chuck Capacity
3/8" (10mm)

Max. Torque
265 in-lbs / 30 Nm

No Load Speed
0-350/0-1350 RPM

3" 2-speed Mini Polisher



ARS1214

Pad Diameter
3" / 75mm

No Load Speed
0-2600 RPM
0-7300 RPM

Adjustable LED Flashlight



ARL1238

Brightness
8500 Lux

Tool Weight
0.37 lbs / 0.17 kg

2.0 / 4.0 Ah Battery



AB1225LA

AB1225LA-2

*single cell detection design



Digital Torque Wrench



- Peak/trace modes enabled
- Precise and accurate
- Memory/buzzer alerts
- LED flashing alert
- Vibration alert

*features are model specific

Model#	ARM315-3A	ARM315-3i	ARM601-3	ARM303-3A	ARM317-4A	ARM329-4i	ARM601-4	ARM319-6A	ARM321-6A	ARM323-8A
Drive Size	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"	1/2"	3/4"	3/4"	1"
Calibration Mode	✓	✓		✓	✓	✓		✓	✓	✓
Angle Measurement	✓			✓	✓			✓	✓	✓
Interchangeable Head		✓				✓				
Torque Range (ft-lbs)	5 - 99.5	10 - 99.5	3.7 - 37	12.5 - 205.7	5 - 99.5	14.8 - 147.5	14.8 - 147.5	44.3 - 442.8	73.8 - 738	73.8-738
Length	17-1/16"	16-3/4"	12-3/8"	26-1/4"	17-7/8"	22"	17-5/16"	37"	48-5/8"	48-13/16"



Digital Torque Adapter



Model#	ARM602-3	ARM602-4	ARM602-4A
Drive Size	3/8"	1/2"	1/2"
Peak/Track Modes	✓	✓	✓
Accuracy	±2% CW, ±3% CCW*	±2% CW, ±3% CCW*	±1.5% CW, ±2.5% CCW*
Torque Range (ft-lbs)	5.9 - 59	14.8-147.6	25-250
Buzzer/LED Alert	✓	✓	✓

