



### Ordering data

6SL3210-5BE23-0UV0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	General tech. specifications
<b>Input</b>	<b>Power factor <math>\lambda</math></b> 0.72
<b>Number of phases</b> 3 AC	<b>Offset factor <math>\cos \varphi</math></b> 0.95
<b>Line voltage</b> 380 ... 480 V +10 % -15 %	<b>Efficiency <math>\eta</math></b> 0.98
<b>Line frequency</b> 47 ... 63 Hz	<b>Ambient conditions</b>
<b>Output</b>	<b>Cooling</b> External fan
<b>Number of phases</b> 3 AC	<b>Installation altitude</b> 1000 m
<b>Rated voltage</b> 400 V	<b>Ambient temperature</b>
<b>Rated power (HO)</b> 3.00 kW / 4.00 hp	<b>Operation</b> -10 ... 60 °C (14 ... 140 °F)
<b>Rated power (LO)</b> 3.00 kW / 4.00 hp	<b>Storage</b> -40 ... 70 °C (-40 ... 158 °F)
<b>Rated current (HO)</b> 7.30 A	<b>Relative humidity</b>
<b>Rated current (LO)</b> 7.30 A	<b>Max. operation</b> 95 %
<b>Rated current (HO) at 480V</b> 7.30 A	<b>Communication</b>
<b>Rated current (LO) at 480V</b> 7.30 A	<b>Communication</b> USS, Modbus RTU
<b>Pulse frequency</b> 2 kHz	<b>Standards</b>
<b>Output frequency</b> 0 ... 550 Hz	<b>Compliance with standards</b> CE, cULus, C-tick, KC
	<b>CE marking</b> EN 61800-5-1 /EN 60204-1 and EN 61800-3

### Overload capability

#### Low Overload (LO)

110 % rated output current for 60 s, cycle time 300 s

#### High Overload (HO)

150 % rated output current for 60 s, cycle time 300 s



Ordering data

6SL3210-5BE23-0UV0

### Mechanical data

Mounting position	Push-through mounting, wall mounting, side-by-side mounting
Degree of protection	IP20
Size	FSB
Net weight	1.60 kg
Width	140.0 mm
Height	160.0 mm
Depth	164.5 mm

### Connections

#### Max. motor cable length

Shielded	25 m
Unshielded	50 m

### Inputs/ outputs

#### Standard digital inputs

Number	4
--------	---

#### Digital outputs

Number as relay changeover contact	1
Number as transistor	1

#### Analog inputs

Number	2 (Can be used as additional digital input)
--------	---

#### Analog outputs

Number	1
--------	---