

## AIR TREATMENT UNITS (FRLs) & AIR HOSES

### AIR LINE FILTERS

To protect valves, pump motors or pneumatic tools from damage or wear caused by dirt and moisture contained in compressed air. Semiautomatic bleeding valve.



### AIR TREATMENT COMPONENTS Ø 1/4"

Maximum working pressure 12 bar. Connection threads: 1/4" BSP (FF).

**240 000** Combined air filter, regulator and lubricator, Ø 1/4"

**240 500** Combined air filter, regulator, Ø 1/4" 0 to 12 bar.

**240 201** Air line regulator, Ø 1/4" Without pressure gauge.

**240 200** Air line regulator, Ø 1/4" With pressure gauge.

**240 300** Air filter, Ø 1/4" Semiautomatic bleeding.

**240 400** Air lubricator, Ø 1/4"

### PRESSURE REGULATOR

To maintain a selected air pressure constant (between 0 to 12 bar) eliminating over pressure risks and erratic operation of equipment. Also available combined with an air filter forming a compact unit.



### AIR TREATMENT COMPONENTS Ø 1/2"

Maximum working pressure 12 bar. Connection threads: 1/2" BSP (FF) with 1/2" BSP (M) - 3/8" BSP (F) adaptors.

**241 001** Combined air filter, regulator and lubricator, Ø 1/2"

**241 501** Combined air filter, regulator, Ø 1/2" 0 to 12 bar.

**241 201** Air line regulator, Ø 1/2" 0 to 12 bar.

**241 301** Air filter, Ø 1/2" Semiautomatic bleeding.

**241 401** Air lubricator, Ø 1/2"

### AIR LINE LUBRICATORS

To create an oil mist that helps increase service life of pumps and other air tools. Oil fill port on top and oil mist adjustment knob.



### AIR TREATMENT COMPONENTS Ø 3/4"

Maximum working pressure 16 bar. Connection threads: 3/4" BSP (FF).

**242 102** Combined air filter - regulator and lubricator, Ø 3/4"

**242 202** Air line regulator, Ø 3/4" 0 to 12 bar.

**242 302** Air filter, Ø 3/4" Semiautomatic bleeding.

**242 402** Air lubricator, Ø 3/4"

### AIR HOSES

Low pressure hoses for compressed air with female swaged fitting and double male adaptor.



PART No.	LENGTH	INT. Ø	CONNECTION THREADS	WORKING PRESSURE
246 006	0,6 m	1/4" - 6 mm	1/4" BSPT (MM)	15 bar
246 010	1,0 m	1/4" - 6 mm	1/4" BSPT (MM)	15 bar
246 015	1,5 m	1/4" - 6 mm	1/4" BSPT (MM)	15 bar
246 030	3,0 m	1/4" - 6 mm	1/4" BSPT (MM)	15 bar
246 060	6,0 m	1/4" - 6 mm	1/4" BSPT (MM)	15 bar
246 100	10,0 m	1/4" - 6 mm	1/4" BSPT (MM)	15 bar
246 150	15,0 m	1/4" - 6 mm	1/4" BSPT (MM)	15 bar
247 706	0,6 m	3/8" - 10 mm	3/8" BSPT (M) - 1/2" BSPT (M)	15 bar
247 710	1,0 m	3/8" - 10 mm	3/8" BSPT (M) - 1/2" BSPT (M)	15 bar
247 715	1,5 m	3/8" - 10 mm	3/8" BSPT (M) - 1/2" BSPT (M)	15 bar

# PETRO Contact Information

## AFRICA

### South Africa

Factory 14 Bentonite Street  
Alrode, Alberton, Johannesburg  
South Africa  
P: +27 (0)11 864 7758  
F: +27 (0) 11 864 1649  
E: sales@petroindustrial.co.za

# PETRO INDUSTRIAL



[petroind.co.za](http://petroind.co.za)