



High pressure grease control guns with ergonomic body and trigger designed to reduce operator hand fatigue. Manufactured in aluminium with steel insert for high pressure. Maximum working pressure: 500 bar (7,150 psi). Inlet thread: 1/4" BSP (F). Outlet thread: 1/8" BSP (F).

GREASE CONTROL GUNS

413 077 Grease control gun

Grease control gun with rigid outlet with 3 jaw connector (PN 121 050).

413 080 Grease control gun with z-swivel

Grease control gun with z-swivel (PN 414 300), rigid outlet and 3 jaw connector assembly (PN 741 300).

413 081 Grease control gun

Grease control gun with 450 mm double steel braid reinforced rubber hose (PN 140 050) with 3 jaw connector (PN 121 050).

413 082 Grease control gun with z-swivel

Grease control gun with z-swivel (PN 414 300) and 450 mm double steel braid reinforced rubber hose (PN 140 050) with 3 jaw connector (PN 121 050).

ELECTRONIC-METERED GREASE CONTROL GUNS

415 002 High pressure grease electronic-metered control gun Includes:

Double steel braid reinforce rubber hose (400 mm) with hydraulic grease connector and Z-swivel.

415 000 High pressure grease electronic-metered control gun Includes:

Z-swivel, with no outlet accessories.



GREASE CONTROL GUN SWIVELS

Equipped with ball bearings for easy articulation even at high pressure. For best results, use a straight swivel between the pump and distribution hose and Z swivel between the hose and grease control gun. Maximum working pressure: 500 bar (7,150 psi).

414 100 Straight grease swivel. 1/4" BSP (MF).

414 200 "L" grease swivel. 1/4" BSP (MF).

414 300 "Z" grease swivel. 1/4" BSP (MF).



GREASE CONTROL GUN OUTLETS

741 306

Rigid outlet with hydraulic grease connector.

741 300

Rigid outlet with 3 jaw hydraulic grease connector (121 050).

140 050

Double steel braid reinforced grease hose, 450 mm.

741 304

Rigid outlet.



OVAL GEAR IN LINE GREASE METER WITH ELECTRONIC DIGITAL DISPLAY

411 100 In line grease meter

High pressure oval gear meter with digital display. Batch display in grams (up to 9999 g) and permanent totalizer in kilograms (up to 999999 kg).

Works with two 1,5 V AAA alkaline batteries. Maximum pressure: 500 bar (7,140 psi). Maximum flow range: up to 1 kg/min (2.2 lb/min).

Accuracy: $\pm 3,0\%$. Inlet and outlet connections: 1/8" BSP (F).

OIL BARS, SPIGOT VALVES & OTHER FLUID DISPENSE GUNS



OIL BAR AND SPIGOT VALVE

361 200 Oil bar

Oil bar to dispense up to four products. Delivered with one outlet, up to three additional outlets can be mounted.

361 100 Oil spigot valve

For connecting to pumps outlet. Connection thread 3/4" BSP (M).

361 110 Additional outlet for oil bars

366 550 In-line meter kit for oil bars

WATER GUNS

For use only with water and antifreeze solutions.

186 000 Water gun

Maximum working pressure 10 bar, connection thread 1/4" BSP (F).

185 001 Wash gun

Maximum working pressure 30 bar, connection thread 1/2" BSP (F).

186 010 Water bib

Maximum working pressure 10 bar, connection thread 1/4" BSP (F).

SPRAY GUNS

187 000 Spray gun. Min. - max. pressure: 3 to 10 bar, connection thread 1/4" BSP (F). Aluminium gun body and 1 liter aluminium container.

187 001 S pray gun. Min. - max. pressure: 3 to 10 bar, connection thread 1/4" BSP (F). Aluminium gun body, metal outlet and 1 liter plastic container.

184 000 Spray gun. Min. - max. pressure: 4 to 10 bar, connection thread 1/4" BSP (F). Plastic gun body, metal outlet and 0.75 liter plastic container.

184 050 Spray gun. Min.- max. pressure: 4 to 10 bar, connection thread 1/4" BSP (F). Plastic gun body, plastic outlet and 0,75 liter plastic container.



INDUSTRIAL QUALITY BLOW GUNS

Aluminium blow guns with anti-slide grip. High air flow and wide range of accessories. Maximum minimum pressure: 3 to 8 bar, connection thread: 1/4" BSP (F). Includes extra-quite nozzle.

188 000 Heavy Duty blow gun

188 100 Compact blow gun

THERMOPLASTIC BLOW GUNS

184 200 Thermoplastic blow gun 1/4" BSP (F).

184 201 Thermoplastic blow gun with flow regulator 1/4" BSP (F).

TIRE INFLATOR GUNS

195 100 Approved tire inflator Tire inflator approved following 86 / 217 CEE directive. 500 mm rubber hose with connecting clip. Connection thread: 1/4" BSP (F).

199 800 Standard tire inflator 650 mm rubber hose with connecting clip. Connection thread: 1/4" BSP (F).

BLOW GUNS ACCESSORIES:

180 801 High flow nozzle

180 802 Extra-quite nozzle (standard in Industrial Quality blow guns).

180 803 Anti splash protection

180 800 150 mm extension tube

Two or more tubes can be combined for getting an extra large tube.

PETRO Contact Information

AFRICA

South Africa

Factory 14 Bentonite Street
Alrode, Alberton, Johannesburg
South Africa
P: +27 (0)11 864 7758
F: +27 (0) 11 864 1649
E: sales@petroindustrial.co.za

PETRO INDUSTRIAL



petroind.co.za