

# 3.7 WATTS- 120V

25-Year

LIMITED WARRANTY



## Cable with plastic guide

Refer to page 3 for installation under soft surfaces.

FLOOR HEATING SYSTEMS

Model	Length		Spacing (ft <sup>2</sup> )		Watt	Amp	Ohms	Guides
			3"	4"				
	Ft.	M	14.8 W	11.2 W				
3,7GCWC-120V-05	16.5	5.05	4.1	5.5	60	0.5	240.0	10
3,7GCWC-120V-10	33	10.1	8.3	11.0	120	1.0	120.0	10
3,7GCWC-120V-14	49.5	15.1	12.4	16.5	180	1.5	80.0	15
3,7GCWC-120V-19	66	20.1	16.5	22.0	240	2.0	60.0	20
3,7GCWC-120V-24	82.5	25.1	20.6	27.5	300	2.5	48.0	20
3,7GCWC-120V-29	99	30.2	24.8	33.0	360	3.0	40.0	20
3,7GCWC-120V-34	115.5	35.2	28.9	38.5	420	3.5	34.3	30
3,7GCWC-120V-38	132	40.2	33.0	44.0	480	4.0	30.0	30
3,7GCWC-120V-43	148.5	45.3	37.1	49.5	540	4.5	26.7	30
3,7GCWC-120V-48	165	50.3	41.3	55.0	600	5.0	24.0	40
3,7GCWC-120V-58	198	60.4	49.5	66.0	720	6.0	20.0	40
3,7GCWC-120V-67	231	70.4	57.8	77.0	840	7.0	17.1	50
3,7GCWC-120V-77	264	80.5	66.0	88.0	960	8.0	15.0	50
3,7GCWC-120V-87	297	90.5	74.3	99.0	1080	9.0	13.3	60
3,7GCWC-120V-96	330	100.6	82.5	110.0	1200	10.0	12.0	60
3,7GCWC-120V-106	363	110.6	90.8	121.0	1320	11.0	10.9	60
3,7GCWC-120V-115	396	120.7	99.0	132.0	1440	12.0	10.0	70
3,7GCWC-120V-125	429	130.8	107.3	143.0	1560	13.0	9.2	70
3,7GCWC-120V-135	462	140.8	115.5	154.0	1680	14.0	8.6	80
3,7GCWC-120V-144	495	150.9	123.8	165.0	1800	15.0	8.0	80

120 V

Includes cable, one floor sensor and plastic cable guides