



25-Year
LIMITED
WARRANTY

3.7 WATTS - 240V

Cable with plastic guide

Refer to page 3 for installation under soft surfaces.

FLOOR HEATING SYSTEMS

240 V

Model	Length		Spacing (ft ²)		Watt	Amp	Ohms	Guides
			3"	4"				
	Ft.	M	14.8 W	11.2 W				
3,7GCWC-240V-10	33.0	10.1	8.3	11.0	120	0.5	480.0	10
3,7GCWC-240V-14	49.5	15.1	12.4	16.5	180	0.8	320.0	15
3,7GCWC-240V-19	66.0	20.2	16.5	22.0	240	1.0	240.0	20
3,7GCWC-240V-24	82.5	25.1	20.6	27.5	300	1.3	192.0	20
3,7GCWC-240V-29	99.0	30.2	24.8	33.0	360	1.5	160.0	20
3,7GCWC-240V-34	115.5	35.2	28.9	38.5	420	1.8	137.1	30
3,7GCWC-240V-38	132.0	40.2	33.0	44.0	480	2.0	120.0	30
3,7GCWC-240V-43	148.5	45.3	37.1	49.5	540	2.3	106.7	30
3,7GCWC-240V-48	165.0	50.2	41.3	55.0	600	2.5	96.0	40
3,7GCWC-240V-53	175.0	53.3	43.8	58.3	650	2.7	88.6	40
3,7GCWC-240V-58	198.0	60.4	49.5	66.0	720	3.0	80.0	40
3,7GCWC-240V-63	208.0	63.4	52.0	69.3	770	3.2	74.8	50
3,7GCWC-240V-67	231.0	70.4	57.8	77.0	840	3.5	68.6	50
3,7GCWC-240V-72	238.0	72.5	59.5	79.3	880	3.7	65.5	50
3,7GCWC-240V-77	264.0	80.4	66.0	88.0	960	4.0	60.0	50
3,7GCWC-240V-82	271.0	82.6	67.8	90.3	1000	4.2	57.6	60
3,7GCWC-240V-87	297.0	90.6	74.3	99.0	1080	4.5	53.3	60
3,7GCWC-240V-96	330.0	100.6	82.5	110.0	1200	5.0	48.0	60
3,7GCWC-240V-106	363.0	110.6	90.8	121.0	1320	5.5	43.6	60
3,7GCWC-240V-115	396.0	120.8	99.0	132.0	1440	6.0	40.0	70
3,7GCWC-240V-126	429.0	130.8	107.3	143.0	1560	6.5	36.9	70
3,7GCWC-240V-135	462.0	140.8	115.5	154.0	1680	7.0	34.3	80
3,7GCWC-240V-145	479.0	146.0	119.8	159.7	1770	7.4	32.5	80
3,7GCWC-240V-154	528.0	161.0	132.0	176.0	1920	8.0	30.0	80
3,7GCWC-240V-173	594.0	181.0	148.5	198.0	2160	9.0	26.7	90
3,7GCWC-240V-192	660.0	201.2	165.0	220.0	2400	10.0	24.0	90
3,7GCWC-240V-212	726.0	221.2	181.5	242.0	2640	11.0	21.8	90
3,7GCWC-240V-231	792.0	241.4	198.0	264.0	2880	12.0	20.0	100
3,7GCWC-240V-250	858.0	261.5	214.5	286.0	3120	13.0	18.5	100
3,7GCWC-240V-270	924.0	281.6	231.0	308.0	3360	14.0	17.1	110
3,7GCWC-240V-289	990.0	301.8	247.5	330.0	3600	15.0	16.0	110

Includes cable, one floor sensor and plastic cable guides