

according to Regulation (EC) No 1907/2006

**Lc 2/21 Antistatic Coolant**

Revision date: 24.10.2017

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Lc 2/21 Antistatic Coolant

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Cleaning agent

**1.3. Details of the supplier of the safety data sheet**

Company name:	LcM GmbH	
Street:	Siemensstrasse 26-28	
Place:	D-32120 Hiddenhausen	
Telephone:	+49 5223 189 66 30	Telefax: +49 5223 189 66 35
e-mail:	info@lcm-gmbh.eu	
Internet:	http://www.lcm-gmbh.eu	

**1.4. Emergency telephone number:**

+49 5223 189 66 30

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Regulation (EC) No. 1272/2008**

Hazard categories:  
 Flammable liquid: Flam. Liq. 2  
 Serious eye damage/eye irritation: Eye Irrit. 2  
 Hazard Statements:  
 Highly flammable liquid and vapour.  
 Causes serious eye irritation.

**2.2. Label elements**

**Regulation (EC) No. 1272/2008**

**Signal word:** Danger

**Pictograms:**



**Hazard statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P235	Store in a well-ventilated place. Keep cool.

**2.3. Other hazards**

No information available.

according to Regulation (EC) No 1907/2006

**Lc 2/21 Antistatic Coolant**

Revision date: 24.10.2017

Page 2 of 8

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Hazardous components**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
64-17-5	ethanol, ethyl alcohol	50 - < 100 %
	200-578-6	603-002-00-5
	Flam. Liq. 2; H225	
67-64-1	acetone; propan-2-one; propanone	10 - < 25 %
	200-662-2	606-001-00-8
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066	

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**After inhalation**

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**After contact with skin**

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

Rinse mouth immediately and drink plenty of water.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

**Unsuitable extinguishing media**

Water.

**5.2. Special hazards arising from the substance or mixture**

Highly flammable. Vapours can form explosive mixtures with air.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

according to Regulation (EC) No 1907/2006

**Lc 2/21 Antistatic Coolant**

Revision date: 24.10.2017

Page 3 of 8

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Advice on storage compatibility**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

**Further information on storage conditions**

Keep cool. Protect from sunlight.

**7.3. Specific end use(s)**

Cleaning agent

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

**8.2. Exposure controls**

according to Regulation (EC) No 1907/2006

**Lc 2/21 Antistatic Coolant**

Revision date: 24.10.2017

Page 4 of 8



**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Protective and hygiene measures**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**Eye/face protection**

Suitable eye protection: goggles.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Flame-retardant protective clothing. Wear anti-static footwear and clothing.

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	green
Odour:	Solvent

**Changes in the physical state**

Initial boiling point and boiling range:	55 °C
Flash point:	<0 °C

**Explosive properties**

negative, no explosion

Lower explosion limits:	2,6 vol. %
Upper explosion limits:	15 vol. %
Density:	0,79 g/cm <sup>3</sup>

**Solubility in other solvents**

The specified parameter for the product is not relevant

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Highly flammable.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

according to Regulation (EC) No 1907/2006

**Lc 2/21 Antistatic Coolant**

Revision date: 24.10.2017

Page 5 of 8

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Acute toxicity**

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
64-17-5	ethanol, ethyl alcohol					
	oral	LD50 mg/kg	6200	Rat	IUCLID	
	inhalative (4 h) vapour	LC50	>20 mg/l	Mouse		
67-64-1	acetone; propan-2-one; propanone					
	oral	LD50 mg/kg	5800	Rat	RTECS	
	dermal	LD50 mg/kg	20000	Rabbit	IUCLID	
	inhalative (4 h) vapour	LC50	76 mg/l	Rat		

**Additional information on tests**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**SECTION 12: Ecological information**

**12.1. Toxicity**

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64-17-5	ethanol, ethyl alcohol					
	Acute crustacea toxicity	EC50 mg/l	9268 - 14221	48 h	Daphnia magna	IUCLID
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	

**12.2. Persistence and degradability**

The product has not been tested.

**12.3. Bioaccumulative potential**

The product has not been tested.

according to Regulation (EC) No 1907/2006

**Lc 2/21 Antistatic Coolant**

Revision date: 24.10.2017

Page 6 of 8

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
64-17-5	ethanol, ethyl alcohol	-0,31
67-64-1	acetone; propan-2-one; propanone	-0,24

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The product has not been tested.

**12.6. Other adverse effects**

No information available.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

**Contaminated packaging**

Wash with plenty of water. Completely emptied packages can be recycled.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

- 14.1. UN number:** UN 1993
- 14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.(ethanol, ethyl alcohol)
- 14.3. Transport hazard class(es):** 3
- 14.4. Packing group:** II
- Hazard label: 3



- Classification code: F1
- Special Provisions: 274 601 640D
- Limited quantity: 1 L
- Excepted quantity: E2
- Transport category: 2
- Hazard No: 33
- Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

- 14.1. UN number:** UN 1993
- 14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.(ethanol, ethyl alcohol)
- 14.3. Transport hazard class(es):** 3
- 14.4. Packing group:** II
- Hazard label: 3



- Classification code: F1

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Lc 2/21 Antistatic Coolant

Revision date: 24.10.2017

Page 7 of 8

Special Provisions: 274 601 640D  
 Limited quantity: 1 L  
 Excepted quantity: E2

#### Marine transport (IMDG)

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.(ethanol, ethyl alcohol)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Special Provisions: 274  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S.(ethanol, ethyl alcohol)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Special Provisions: A3  
 Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

#### 14.6. Special precautions for user

Warning: Combustible liquid.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: ethanol, ethyl alcohol; acetone; propan-2-one; propanone

2010/75/EU (VOC): 100 %

2004/42/EC (VOC): 100 %

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Lc 2/21 Antistatic Coolant

Revision date: 24.10.2017

Page 8 of 8

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).  
Water contaminating class (D): 1 - slightly water contaminating

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method

#### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
EUH066 Repeated exposure may cause skin dryness or cracking.

#### Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*