

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Haynes Silicone Spray

SDS Number: 100, 100-6 Revision Date: 10/20/2022

Version: 2

1

Product Type: Aerosol Industrial Lubricant

Supplier Details: Haynes Manufacturing Company

24142 Detroit Road

Westlake, OH 44145

Phone: 440-871-2188

Emergency: 440-871-2188 x195

NOTE: The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Gases Under Pressure, Liquefied Gas

Physical, Flammable Aerosols, 1

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:





GHS Hazard Statements:

3

H280 - Contains gas under pressure; may explode if heated

H222 - Extremely flammable aerosol

GHS Precautionary Statements:

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P410 + P403 - Protect from sunlight. Store in a well-ventilated place.

P412 - Do not expose to temperatures exceeding 50 °C/ 122 °F.

P501 - Dispose of contents/container in accordance with local/regional regulations.

COMPOSITION/INFORMATION OF INGREDIENTS

CAS#		l Ingredients: Chemical Name:
68476-86-8	85-95%	Petroleum gases, liquefied
63148-62-9	5-15%	Dimethylpolysiloxane

4 FIRST AID MEASURES





Inhalation: Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.

Skin Contact: Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek

medical attention.

Eye Contact: Flush with warm water for 15 minutes. Seek medical attention.

Ingestion: Seek medical attention. If individual is drowsy or unconscious, do not give

anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce

vomiting. If possible, do not leave individual unattended.

5 FIRE FIGHTING MEASURES

Flash Point: Flash point of propellant <0 degrees F.

LEL: Lower: 3.4 % (VOL.) Gas in air (propellant portion)
UEL: Upper: 18 % (VOL.) Gas in air (propellant portion)

Extinguishing Media:

Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials. Unusual Fire & Explosion Hazards:

This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite. Special Fire Fighting Procedures:

At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

ACCIDENTAL RELEASE MEASURES

Spill or Leak Instructions

6

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

HANDLING AND STORAGE

Handling Precautions: Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not

puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated

leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not

incinerate

Storage Requirements: Store in a cool, dry area, away form heat or direct sunlight. Keep containers closed when not in use. Do

not store with incompatible materials



Safety Data Sheet

Haynes Silicone Spray

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure.

Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to

maintain exposures below TLV levels.

Personal Protective Equipment:

Protective Equipment:

Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always

use ANSI approved safety glasses or splash shield.

Respiratory Protection:

Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its

components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above exposure levels an approved self-contained breathing apparatus or airline

respirator with full face-piece is required

Other Suggested Equipment:

Eye wash station and emergency showers should be available. Spill containment equipment should be

available.

Discretion Advised:

We, take no responsibility for determining what measures are required for personal protection in any

specific application. The general information should be used with discretion.

Liquefied Petroleum Gas 68476-86-8 85-95 % OSHA (PEL) 1000 ppm

ACGIH TLV 1000 ppm

Dimethylpolysiloxane 63148-62-9 5-15% NE

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear Aerosol

Viscosity:NEOdor:NegligibleBoiling Point:NESolubility:NegligibleFlammability:FlammableFreezing/Melting Pt.:NE

Vapor Pressure: >30 psi **Flash Point:** Flash point of propellant < 0°F

pH: NE Vapor Density: >1 Air = 1

Evap. Rate: Ether = 1 Slower

Decomp Temp: NE

10 STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to Avoid: Heat, spark, and open flame.

Materials to Avoid: Strong Oxidizing Agents.

Hazardous Decomposition: Combustion will produce Carbon Monoxide, Carbon Dioxide, and nitrogen-oxygen compounds.

Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

Dimethylpolysiloxane cas#:(63148-62-9) [5-15%]

Information on toxicological effects

Acute toxicity: no data available

Inhalation: no data available

SDS Number: Haynes 06-983-12 Page: 3 / 6 Revision Date: 10/20/2022





Dermal: no data available

Skin corrosion/irritation: Skin - rabbit Result: Mild skin irritation - 24 h

Serious eye damage/eye irritation: Eyes - rabbit Result: Mild eye irritation - 24 h

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: JT6485000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

12 ECOLOGICAL INFORMATION

Dimethylpolysiloxane cas#:(63148-62-9) [5-15%]

Information on ecological effects

Toxicity: no data available

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.

13 DISPOSAL CONSIDERATIONS

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.



Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

14

TRANSPORT INFORMATION

Aerosols (limited quantity), Class 2.1, ERG 126

AIR (IATA) Aerosols (limited quantity), Class 2.1, ERG 126, UN No. 1950

Vessel Aerosol (Limited Quantity), Class 2.1, UN No 1950

15

REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[85-95%] Petroleum gases, liquefied (68476-86-8) TSCA

[5-15%] Dimethylpolysiloxane (63148-62-9) TSCA

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory Code Legend

TSCA = Toxic Substances Control Act

16

OTHER INFORMATION

NFPA: Health = 1, Fire = 4, Reactivity = 0, Specific Hazard = n/a



Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.

Revision Date: 10/20/2022