

DL (Dry Lock) Port System Charts for Fujifilm X-Mount Mirrorless Cameras

PORT OPTIONS

Some lenses have more than one port option. The first column is always the recommended option for the best compromise of imaging quality, performance, and handling with any given lens.

PRODUCT(S) REQUIRED

Where multiple lines of products are listed for a given option, all products listed are required to make a complete compatible lens port.

LENSES REFERENCING "+4 DIOPTER REQUIRED"

A +4 diopter is available for purchase through your local camera store, and is commonly sold in a set with +1 and +2 close-up lenses. Common brands include Tiffen and Hoya. Make sure to purchase the correct size for your lens. The thread diameter is usually referenced on the front of the lens in millimeters (ø 58mm, 67mm, etc.). All photos will be out of focus if a +4 diopter is required but not used.

Fujifilm X-mount Lenses

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
8-16 mm Fujifilm XF f/2.8 R LM WR	Larger dome is best for split shots (half-in, half-out of the water). Zoom solution is not currently available. Lens must be used at a fixed focal length. AF only. Product(s) required: 75340 Dome Port 75020 Extension 75037 Extension	Compact and lightweight for travel. Better for close focus wide angle. Zoom solution is not currently available. Lens must be used at a fixed focal length. AF only. Product(s) required: 75344 Dome Port 75020 Extension 75037 Extension	
10-24 mm Fujifilm XF f/4 R OIS	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75042 Extension 5509.28 Zoom Gear	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Dome Port 75042 Extension 5509.28 Zoom Gear	
14 mm Fujifilm XF f/2.8 R	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Dome Port	
16 mm Fujifilm XF f/1.4 R	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Dome Port	
18 mm Fujifilm XF f/2 R	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Dome Port	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
16-80 mm Fujifilm XF f/4 R OIS WR	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: +4 Diopter Required 75340 Dome Port (2) 75028 Extension 5509.31 Zoom Gear	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: +4 Diopter Required 75344 Dome Port 75020 Extension 75042 Extension 5509.31 Zoom Gear	
18-55 mm Fujifilm XF f/2.8-4 R LM OIS	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: +4 Diopter Required 75344 Dome Port 75050 Extension 5509.27 Zoom Gear	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: +4 Diopter Required 75340 Dome Port 75050 Extension 5509.27 Zoom Gear	
23 mm Fujifilm XF f/1.4 R	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Dome Port	
50 mm Zeiss Touit f/2.8M Macro	Port recommendation not yet available.		
60 mm Fujifilm XF f/2.4 R Macro	Port recommendation not yet available.		
80 mm Fujifilm XF f/2.8 R LM OIS WR Macro	AF only. Product(s) required: 75301 Flat Port 75050 Extension		