


# M Series

## Specification

### Dimensions



### Finishes




**Black Exterior,  
Black Interior**

Zinc Alloy Trim  
Polycarbonate Lens

**Satin Chrome Exterior,  
Satin Chrome Interior**

Zinc Alloy Trim  
Polycarbonate Lens

### Lever Styles



**Standard**

**Return**

## Features

<b>Credential Types</b>	Smartphone, NFC Keycard, Doorcode, Mechanical Key
<b>Users</b>	1500
<b>Management</b>	App and Cloud

## Communication

<b>Wireless Standards</b>	Bluetooth Low Energy 5.0 (BLE), Near Field Communication (NFC)
<b>NFC Frequency</b>	13.56 MHz
<b>NFC Type</b>	MIFARE DESFire Light
<b>Supported Devices</b>	iOS, Watch OS, and Android (see website for full list of supported devices)

## Power

<b>Power Supply</b>	6 AA non-rechargeable alkaline batteries
<b>Battery Status</b>	Passive monitoring and active notifications via LatchOS
<b>Inductive Jumpstart</b>	"Qi-compatible power source can wireless power a Bluetooth unlock in the event of battery failure

## Environmental

<b>Operating Temperature</b>	Interior: -20°C to 54°C
<b>Operating Humidity</b>	0–95% relative humidity, non-condensing
<b>Weather Resistance</b>	Lens: IP65, Exterior/Interior Assemblies: IP55 — Interior assembly not intended for outdoor use

## Certifications and Warranty

<b>Certifications</b>	UL 10B/C (90 min), CAN/ULC S104, FCC Part 15, IC RSS, FL TAS 201/202/203-94, Built to ANSI/BHMA 156.13 Grade 1
<b>Compliance</b>	Complies with Americans with Disabilities Act
<b>Warranty</b>	2-year limited warranty on electronic components, 5-year limited warranty on mechanical components

## Mechanical Specifications

<b>Lock Format</b>	Mortise
<b>Handing</b>	Field reversible
<b>Door Thickness Compatibility</b>	1-3/4" / 44.5mm
<b>Backset Compatibility</b>	2-3/4" / 69.9mm
<b>Door Preparation</b>	<a href="http://www.support.latch.com">www.support.latch.com</a>
<b>Deadbolt Throw</b>	1" / 25.4mm
<b>Faceplate Options</b>	8" x 1/4", 0.06" Thick / 203.2 x 6.4 mm, 1.5mm Thick
<b>Strike Plate</b>	ANSI 4-7/8" x 1-1/4" / 123.8 x 31.75 mm Curved Lip Strike