
## LATCH

# Latch Intercom

Specifications

#### Dimensions



#### Power

DC 2-wire	12 - 24VDC
Power Over Ethernet	802.3bt with 50W+
Power Consumption	Typical: 20W, max: 50W

#### Features

Intuitive user interface with tactile buttons

Receive audio calls at any US phone number

Receive video and audio calls in the Latch App (video requires external camera)

Remote unlock

Compatible with the Fanvil i10d in-unit PBX receiver

Flexible connectivity options: Ethernet, Wi-Fi, and Cellular

#### Screen

Brightness	1000 nits, automatic brightness adjustment
Viewing Angle	176 degrees
Size	7-inch diagonal
Protection	Anti-reflection, anti-fingerprint Made with Corning® Gorilla® Glass 3

## Audio and Video

Loudness	Automatic volume adjustment, 90dB max volume
Microphone	Automatic sensitivity adjustment, dual microphone, echo cancellation, and noise reduction
Supported Cameras	Works with Latch camera

## Communication

Ethernet	10/100/1000 mbps
Wi-Fi	2.4/5 GHz, 802.11a/b/g/n/ac
Cellular	Category 1
Bluetooth	Bluetooth 4.2
IP Address	DHCP or Static IP

#### Environmental

Operating Temperature	-30°C to 60°C
Dust and water resistance	IP65

## **Certifications and Compliance**

Certifications	FCC Part 15 Subpart B/C/E, FCC Part 24, IC RSS-130/133/139/247, PTCRB, UL62368-1, UL294, IP65
Warranty	5 Year
Compliance	Complies with American Disabilities Act

## **Mechanical Specifications**

Dimensions	12.82 x 6.53 x 1.38 in inches 325.6 x 166.0 x 35.1 in mm
Materials	Stainless steel, glass fiber reinforced resin, and impact-resistant glass