



EXTRA MAX



Good performance at low price
GO Fast with tight budget

ETS Racing Fuels uses most efficient pure components (purity > 98 %) in order to guaranty consistency of physical parameters and absolutely identical chemical composition of our fuels, batch to batch. This ensures to our customer's to get the highest results of their engine mapping along the season.

Get the most of your engine's performance and reliability... choose ETS Racing Fuels

APPLICATIONS

- ☒ Unleaded Racing Fuel especially blended for 4 strokes engines.
High octane fuel especially blended for supercharged and turbo charged engines or natural aspirated engines with high compression ratio.
- ☒ Complies with the FIA 2014 Appendix J Art.252 Paragraph 9
- ☒ Thanks to a selection of the most efficient pure chemicals and additives, this fuel offers the best consistency to engine performances with respect to the regulation.
Due to its high combustion speed and high combustion energy, EXTRA MAX fuel develops performances especially during transient phases giving better acceleration.

RECOMMENDATION

- ☒ Air/fuel ratio, supercharging pressure and ignition advance must absolutely be checked and retuned to reach optimum performances. Ignition and injection mapping are strongly recommended.
- ☒ In order to maintain the original properties, and according to Health and Safety regulations of commercial fuels, this gasoline shall be handled and stored in a cool place, well ventilated, away from any source



#todoenmotorsport



SPECIFICATION

Characteristics	Standards	Typical results	FIA Appendix J Specifications
RON	ASTM D 2699	101.5	95 - 102
MON	ASTM D 2700	90	85 - 90
Oxygen content	Elemental analysis	3.6	3,7 % max
Nitrogen content	ASTM D 3228	<0.1	0,5 % max
Peroxides	ASTM D 3703	Traces	100 ppm max
Lead content	ASTM D 3341	<0.005	13 mg / L max
Benzene content	ASTM D 3606	<0.01	1 % max
Reid vapour pressure	ASTM D 323	46	80 KpA max
Distillation at 70°C	ASTM D 86	33	
Distillation at 100°C	ASTM D 86	68	30 % - 72 %
Distillation at 150°C	ASTM D 86	100	75 % minimum
Final boiling point	ASTM D 86	125	210 °C max
Specific gravity at 15°C	ASTM D 4052	756	720 - 785 Kg / m ³

Do you want to know more about EXTRA MAX racing fuel, such as performance vs competitor fuels or vs other ETS fuels?

Check out our interactive website [WWW.ETS - RACING.COM](http://WWW.ETS-RACING.COM)

If you are already one of our customers, log in to have full access to information and recommendations.

Anyway, don't hesitate to contact us for any detail:

ets@vlmotorsport.com

