

## SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS #: 082629

# HTX 3835

Date of the previous version: 2016-01-22

Revision Date: 2016-01-22

Version 2

1. IDENTIFICATION				
Product identifier				
Product name	HTX 3835			
Other means of identification				
Product Code(s)	082629			
Number Substance/mixture	D5O Mixture			
Recommended use of the chemical and restrictions on use				
Identified uses	Motor oil.			
Uses advised against	Do not use for any purpose other than the one for which it is intended			
Details of the supplier of the safety data sheet				
Supplier Address	TOTAL Specialties USA Inc 1201 Louisiana Street, Suite 1800 Houston, TX 77002 Phone: +1 800 323 3198			
Contact Point	Technical/ HSEQ			
E-mail Address	USRMLIN-info@total.com			
Emergency telephone number Company Phone Number Emergency telephone 2. HAZARDS IDENTIFICATIO	+1 (908) 862-9300 CHEMTREC: +1 800 424 9300 (24h)			

#### **Classification**

Skin sensitization - Category 1

#### Label elements

Date of the previous version: 2016-01-22

Revision Date: 2016-01-22

**HTX 3835** 

Version 2



#### WARNING

May cause an allergic skin reaction

#### **Precautionary Statements - Prevention**

Avoid breathing dust/fume/gas/mist/vapours/ spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves

#### **Precautionary Statements - Response**

Specific treatment (see Section 4 on this label) **Skin** IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

#### **Precautionary Statements - Disposal**

Dispose of contents/ container to an approved waste disposal plant

## Unknown Acute Toxicity

No information available

#### Hazards not otherwise classified (HNOC)

None known

Other information Physical-Chemical Properties	Contaminated surfaces will be extremely slippery.
Environmental properties	Should not be released into the environment.

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### <u>Mixture</u>

#### Chemical nature

The product is made from synthetic base oils (Polyalfaolefins).

Chemical Name	CAS-No	Weight %
Molybdene dithiocarbamide complex, polysulfur	~~	<1
alkyl long chain		



# HTX 3835

Date of the previous version: 2016-01-22

Revision Date: 2016-01-22

Version 2

## 4. FIRST AID MEASURES

First aid measures for different exposure routes				
General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.			
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.			
Skin contact	Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse.			
Inhalation	Move to fresh air.			
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.			
Most important symptoms/effects,	acute and delayed			
Skin contact	May cause an allergic skin reaction.			
Eye contact	Not classified.			
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.			
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.			
Symptoms	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.			
Indication of immediate medical at	ttention and special treatment needed, if necessary			
Notes to physician	Treat symptomatically.			
5. FIRE-FIGHTING MEASURES				
Suitable Extinguishing Media	Carbon dioxide (CO2). ABC powder. Foam. Water spray or fog.			
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.			
Special Hazard	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may			

be highly dangerous if inhaled in confined spaces or at high concentration.

Explosion Data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.



SDS #	:	082629
-------	---	--------

HTX 3835

Date of the previous version: 2016-01-22

Revision Date: 2016-01-22

Version 2

Protective Equipment and<br/>Precautions for FirefightersAs in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH<br/>(approved or equivalent) and full protective gear. Evacuate non-essential personnel.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information	Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.
Other information	See Section 12 for additional information.
Environmental precautions	
General Information	Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained. See Section 12 for additional Ecological Information.
Methods and materials for containn	nent and cleaning up
Methods for cleaning up	Dam up, Contain spillage, and then collect with non-combustible absorbent material. (e.g.

Methods for cleaning up Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

#### 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handlingWhen using, do not eat, drink or smoke. For personal protection see section 8. Use only in<br/>well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes<br/>and clothing.Prevention of fire and explosionTake precautionary measures against static discharges: Ground/bond containers, tanks<br/>and transfer/receiving equipment.Hygiene measuresEnsure the application of strict rules of hygiene by the personnel exposed to the risk of<br/>contact with the product. Regular cleaning of equipment, work area and clothing is<br/>recommended. Wash hands and face before breaks and immediately after handling the<br/>product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been

#### Conditions for safe storage, including any incompatibilities

Technical measures/Storage<br/>conditionsKeep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep<br/>container tightly closed. Keep preferably in the original container. Otherwise reproduce all<br/>indication of the regulation label on the new container. Do not remove the hazard labels of<br/>the containers (even if they are empty). Design the installations in order to avoid accidental<br/>emissions of product (due to seal breakage, for example) onto hot casings or electrical<br/>contacts. Protect from frost, heat and sunlight. Protect from moisture.

contaminated with product. Do not put product contaminated rags into workwear pockets.



# HTX 3835

Date of the previous version: 2016-01-22

Revision Date: 2016-01-22

Version 2

Materials to Avoid

Strong oxidizing agents.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

.

Exposure limits

Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m<sup>3</sup>, NIOSH (REL) TWA 5 mg/m<sup>3</sup>, STEL 10 mg/m<sup>3</sup>, ACGIH (TLV) TWA 5 mg/m<sup>3</sup> (highly refined).

Exposure controls	
Engineering Measures	Apply technical measures to comply with the occupational exposure limits.
Individual protection measures, su	ch as personal protective equipment
General Information	If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.
Eye/Face Protection	If splashes are likely to occur, wear:. Safety glasses with side-shields.
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.
Hand Protection	Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Respiratory protection	None required under normal usage. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands and face before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

## 9. PHYSICAL AND CHEMICAL PROPERTIES



# HTX 3835

Date of the previous version: 2016-01-22

Revision Date: 2016-01-22

Version 2

#### **Physical and chemical properties**

Appearance Color Physical State @20°C Odor Odor Threshold		limpid amber liquid Characteristic No information available	
<u>Property</u> pH Melting point/range	Values_	<u>Remarks</u> Not applicable Not applicable	<u>Method</u>
Boiling point/boiling range		No information available	
Flash point	<b>244 °C</b> 471 °F		Cleveland Open Cup (COC) Cleveland Open Cup (COC).
Evaporation rate Flammability Limits in Air upper Lower Vapor Pressure Vapor density Relative density Density Water solubility Solubility in other solvents logPow Autoignition temperature Decomposition temperature	0.852 852 kg/m <sup>3</sup>	No information available No information available No information available No information available No information available @ 15 °C @ 15 °C Insoluble No information available No information available No information available No information available	Cieveland Open Cup (COC).
Viscosity, kinematic Explosive properties Oxidizing Properties Possibility of hazardous reactions <u>Other information</u>	72.2 mm2/s 12.2 mm2/s Not explosive Not applicable No information available	@ 40 °C @ 100 °C	ISO 3104 ISO 3104

**Freezing Point** 

No information available

# 10. STABILITY AND REACTIVITYReactivityNo information available.Chemical stabilityStable under recommended storage conditions.Possibility of hazardous reactionsNone under normal processing.Conditions to AvoidHeat (temperatures above flash point), sparks, ignition points, flames, static electricity.Incompatible MaterialsStrong oxidizing agents.



HTX 3835

Date of the previous version: 2016-01-22

Revision Date: 2016-01-22

Version 2

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

#### 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Principle Routes of Exposure	Inhalation, Ingestion, Eye contact, Skin contact.
Symptoms	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Skin contact	May cause an allergic skin reaction.
Eye contact	Not classified.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Acute toxicity - Product Information

**Product Information** Product does not present an acute toxicity hazard based on known or supplied information.

Oral	Not classified.
Dermal	Not classified
Inhalation	Not classified

#### Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Molybdene dithiocarbamide	LD50 > 2000 mg/kg (Rat - OECD	LD50 > 2000 mg/kg (Rat - OECD	
complex, polysulfur alkyl long chain	425)	402)	

May cause an allergic skin reaction. This product is not classified carcinogenic. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

Sensitization

Carcinogenicity



# HTX 3835

Date of the previous version: 2016-01-22

Revision Date: 2016-01-22

Version 2

Reproductive toxicity Other adverse effects This product does not present any known or suspected reproductive hazards. Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing). Not classified.

Aspiration Hazard

## **12. ECOLOGICAL INFORMATION**

#### Ecotoxicity Acute aquatic toxicity - Product Information

No information available

#### Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Molybdene dithiocarbamide	EC50 (72h) 14 mg/l	LL50 (96h) 94.8 mg/l	EL50 (48h) 50 mg/l (Daphnia	
complex, polysulfur alkyl	(Selenastrum capricornutum	(Oncorhynchus mykiss -	magna - OECD 202)	
long chain	- OECD 201)	OECD 203)		
~~				

#### Chronic aquatic toxicity - Product Information

No information available

#### Chronic aquatic toxicity - Component Information

No information available

#### Effects on terrestrial organisms No information available.

#### Persistence and degradability

General Information No information available.

#### **Bioaccumulative potential**

**Product Information** No information available.

logPow No information available

#### Component Information

Chemical Name	log Pow
Molybdene dithiocarbamide complex, polysulfur alkyl long chain	5.1
M	

#### **Mobility**



<b>SDS #</b> : 082629	082629 HTX 3835			
Date of the previous version: 2	2016-01-22	Revision Date: 2016-01-22	Version 2	
Soil	Given its phy mobility	vsical and chemical characteristics, the product generally	shows low soil	
Air Water <u>Other adverse effects</u>	Loss by evaporation is limited Insoluble The product spreads on the surface of the water.			
General Information	No information available			
13. DISPOSAL CONSIDER	ATIONS			
Waste treatment				
Waste Disposal Methods	Dispose of ir	accordance with local regulations.		
Contaminated packaging	Empty conta disposal.	iners should be taken to an approved waste handling site	for recycling or	

#### **14. TRANSPORT INFORMATION**

DOT	Not regulated
TDG	Not regulated
<u>MEX</u>	Not regulated
ICAO/IATA	Not regulated
IMDG/IMO	Not regulated
ADR/RID	Not regulated
ADN	Not regulated

## **15. REGULATORY INFORMATION**

## **U.S. Federal Regulations**

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

#### SARA 311/312 Hazard Categories



SDS # :	082629
---------	--------

# HTX 3835

Date of the previous version: 2016-01-22

Revision Date: 2016-01-22

Version 2

Acute Health Hazard	no
Chronic Health Hazard	no
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

#### **Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

#### **U.S. State Regulations**

#### **California Proposition 65**

This product does not contain any Proposition 65 chemicals.

#### U.S. State Right-to-Know Regulations

No information available

#### **16. OTHER INFORMATION**

NFPA	_
HMIS	

Health Hazard 0

Flamm

Flammability 1 Instability 0

Physical Hazard 0

Physical and chemical hazards  $\ -$  Personal protection  $\ X$ 

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Flammability 1

Revision Date: Revision Note 2016-01-22 \*\*\* Indicates updated section



<b>SDS #</b> : 082629	HTX 3835		
Date of the previous version:	2016-01-22	Revision Date: 2016-01-22	Version 2
Abbreviations, acronyms	bw = body weig bw/day = body EC x = Effect C GLP = Good La IARC = Interna LC50 = $50\%$ Le which causes th LD50 = $50\%$ (one half) LL = Lethal Loa NIOSH = Natio NOAEL = No Ob NOEC = No Ob NOEL = No Ob OECD = Organ OSHA = Occup	weight/day Concentration associated with x% response aboratory Practice tional Agency for Research of Cancer ethal concentration - Concentration of a chemical in a he death of 50% (one half) of a group of test animals ethal Dose - Chemical amount, given at once, which c of a group of test animals ading nal Institute of Occupational Safety and Health Observed Adverse Effect Level oserved Effect Concentration iserved Effect Level ization for Economic Co-operation and Development bational Safety and Health Administration ance of unknown or Variable composition, Complex re	ir or a chemical in wate
Legend	Section 8 ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH - National Institute for Occupational Safety and Health TLV - Threshold Limit Values PEL - Permissible Exposure Limits IDHL - Immediately Dangerous to Life or Health concentrations TWA - Time Weight Average STEL - Short Term Exposure Limits S* - Skin notation TSCA - Toxic Substance Control Act		ts

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet