

Lotus Lubes™ T-3 Automatic Transmission Fluid

PRODUCT DESCRIPTION

LOTUS Lubes™ T-3 Transmission Fluid is a premium fluid designed and recommended for use in automatic transmissions previously serviceable by GM DEXRON®-III (H) and Ford MERCON® brands. It may also be used in equipment requiring a Type A fluid, Allison C-4, Caterpillar TO-2 or Ford specifications M2C138-CJ and M2C166-H.

LOTUS Lubes™ T-3 Transmission Fluid's state-of-the-art additive system provides ultimate transmission protection and peak performance in passenger cars, sports utility vehicles and light trucks. It also provides excellent hydraulic performance in industrial applications where low-temperature fluidity or leak detection is an important requirement.

FEATURE & BENEFITS

- * Superior wear protection
- * Excellent frictional properties for smooth shifting
- * Excellent anti-shudder performance
- * Good seal compatibility
- * Protection against varnish and sludge formation
- * Superior thermal stability
- * Outstanding low-temperature performance
- * Formulated with select base stocks for added resistance to thermal breakdown
- * Provides active anti-wear agents to protect critical transmission components
- * Delivers added resistance to fluid oxidation in severe operating conditions
- * Shear-stable viscosity modifiers provide stay-in-grade protection



TYPICAL PHYSICAL PROPERTIES

Density, g/cm ³ @ 15° C	0.860
Flash Point, COC C° (F°)	212 (413)
Pour Point, C° (F°)	-52 (-61)
Viscosity, cP @ -20° C	1300
Viscosity, cP @ -30° C	4200
Viscosity, cP @ -40° C	17000
Viscosity, cSt @ 40° C	35.4
Viscosity, cSt @ 100° C	7.2
Viscosity Index	172
Color	Red
Foam Test, ASTM D892	Pass
Minor variations in typical physical properties may occur from normal manufacturing processes	

APPLICATIONS

LOTUS Lubes™ T-3 Automatic Transmission Fluid is recommended for the following transmission requirements:

- * **Transmissions previously serviceable by GM DEXRON®-III (H) and Ford MERCON® brands**
- * **Allison C-4, Caterpillar TO-2 or Ford specifications M2C138-CJ and M2C166-H**
- * **Not recommended for use in transmissions requiring GM DEXRON®-VI, Ford MERCON®-V, MERCON® SP & LV fluids, or Ford ATF Type F applications**