

NEPTUNA 2T SUPER SPORT

Gasoline engine oil

KEY DATA



✓ Leisure crafts

SPECIFICATIONS AND APPROVALS

International Specifications:

API TC
NMMA TC-W3®

Suitable for:

- ✓ JOHNSON
- ✓ MARINER
- ✓ MERCURY
- ✓ SUZUKI
- ✓ YAMAHA

APPLICATIONS

TOTAL NEPTUNA 2T SUPER SPORT is a semi-synthetic lubricant adapted to **2 strokes gasoline engines**.

It is adapted to all 2 strokes engines, including **direct injection engines**.

The mixing with the fuel should be in accordance with the manufacturer's recommendations.

PERFORMANCES AND CUSTOMER BENEFITS

TOTAL NEPTUNA 2T SUPER SPORT exhibits excellent lubrication guaranteeing **reduced wear**.

Outstanding detergent property helps prevent the clogging of piston ports avoids spark plug fouling and extends engine lifespan.

Its **anti-rust and anti-corrosion** properties protect engines during prolonged stop.

NEPTUNA 2T SUPER SPORT

Gasoline engine oil

PHYSICAL AND CHEMICAL CHARACTERISTICS*

| TEST | UNIT | TEST METHOD | VALUE |
|-------------------------------|--------------------|-------------|-------|
| Density at 15 °C | kg/m ³ | ASTM D1298 | 864 |
| Kinematic Viscosity at 40 °C | mm ² /s | ASTM D445 | 50 |
| Kinematic Viscosity at 100 °C | mm ² /s | ASTM D445 | 8.5 |
| Viscosity Index | - | ASTM D2270 | 146 |
| Pour Point | °C | ASTM D97 | -36 |

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

RECOMMENDATIONS FOR USE

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C.

Exposure to strong sunlight, extreme cold or high temperature variations must be avoided. All packages should be protected from bad weather conditions.

The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed.

It is accessible on request from your local dealer or on the website <http://sdstotalms.total.com>.

This product should not be used for applications other than those for which it is intended. If disposing of used product, take care to protect the environment and comply with local regulations.