



Infant transport incubator

ISOLETTE® T1500

Mobile intensive care unit

APPLICATION

The Isolette TI500 Transport Incubator from Dräger Medical is a self contained, mobile, intensive care unit.

THERMAL PERFORMANCE

Consistent air temperature is essential to the health of a premature infant. The Isolette TI500 Transport Incubator has a double wall design which reduces radiant heat loss from the infant during transport between departments or between hospitals.

INTERGRAL HUMIDITY

Humidity is extremely important, especially for babies less than 26 weeks in gestational age. An integral humidity pad helps minimize the infant's evaporative heat loss by providing 50 to 70 percent humidity in the patient hood for up to 12 hours.

COMMAND & CONTROL

The controller features a display that is easy to read at any angle during transport. Displays for air and skin temperature help you maintain control and provide essential information about the infant's thermal support. Visual indicators for battery power status, power source and system alarm status are designed to keep the caregiver in command.

FLEXIBLE POWER SOURCE

Regardless of whether it is an air or ground transport, power is the last thing you should worry about. The Isolette TI500 Transport Incubator from Dräger Medical operates on AC or DC power, using AC when available or switching to its internal battery when necessary. For extended length transports, the system can be configured with a second internal battery. And of course the Isolette TI500 Transport Incubator also operates on the external DC power found on board emergency transport vehicles.

ACCESS MADE EASY

Access to the infant is quick and easy through the front access door, the head door, or through the Quiet Touch™ port access doors. The head door folds down and the mattress retracts out from the hood to provide access for emergency procedures. An iris port and six tubing ports offer ventilator tubing support and entry possibilities for sensors while keeping the temperature stable.

HOOD OPTIONS

You can choose either a standard hood or a high hood. While both have a low profile, the high hood offers two more inches of clearance through a larger front access door.

INTEGRATED EXAM LIGHT

An integrated exam light provides evenly distributed illumination to the mattress, assisting you in accurate patient assessment during transport.

THE RIGHT SIZE AND WEIGHT

To make transport easy, the Isolette TI500 Transport Incubator is designed to fit into smaller spaces. System weight has also been reduced to enhance mobility and ease access in and out of emergency transport vehicles.



ACCESSORIES

Organizer tray for Resuscitaire slide through drawer	MU11132
Second Battery Option	MU05598

Accessory Shelf

Standard Hood	MU05619
High Hood	MU05841
IV Pole	MU04500
Conversion Kit to High Hood	MU06094

TECHNICAL SPECIFICATIONS ISOLETTE® TI500 INCUBATOR

Physical Attributes (without options/accessories)	TI500	TI500 with 147 stand
Height	20 in (50.8 cm)	min- 32 in (81.3 cm) max- 44 in (111.8 cm)
Width	20.8 in (52.7 cm)	22.3 in (56.5 cm)
Length	37.8 in (95.9 cm)	40.3 in (102 cm)
Weight ⁽¹⁾	108.5 lbs (49.2 kg)	159 lbs (72 kg)
Distance from vertical hood to mattress	Low Hood 8.25 in (21 cm)	High Hood 9.84 in (25 cm)
Standard Features		
Double wall		
Skin temperature probe		
O ₂ inlet		
Examination lamp		
2 access doors		
2 disposable infant restraint straps		
1 Iris port		
2 Quiet Touch™ port doors		
6 tubing ports		
Locking power control receptacles		
DC cable		
2D or 2E size tank mounts		The tank mount permits mounting gas cylinders with a diameter of up to 4.5 in (11.6 cm) and up to 34 in (85 cm) in length
Humidity Pad ²		
Optional Features		
Accessory shelf, IV pole, * High Hood, * Pressure Regulator and Flowmeter		
General Specifications		
O ₂ concentration range		21% to 58% minimum
Humidity capacity		50% to 70%
Noise level		<60 dBA ³
Performance Characteristics		
Temperature set range		22.0 °C–38 °C (71 °F–100 °F)
Temperature rise time		30 minutes
Temperature variability		≤1.0 °C
Temperature overshoot		≤2.0 °C
Temperature uniformity		≤1.0 °C
Correlation of display temperature to set point at temperature equilibrium		≤ 2.0 °C in 10–20 °C ambients ≤1.5 °C in 20–30 °C ambients
Humidity pad		Holds 400 ml.(14 oz) sterile distilled water with no significant spillage for up to 45° tilt in either direction.
Air filter		Removes >99% of airborne particles greater than 0.5 micron diameter
Relative humidity		50 to 70% for 10–12 hours using humidity pad
Check calibration key		36.0 ° ± 0.1 °C
Controller Displays		
On/standby		Illuminates when "On"
Battery condition status		4 LED indication of battery charge condition 25–100%
Power mode		Illuminates AC, DC, or external DC
Heater power		4 LED indication of heater power; 25–100%
Baby temperature °C		Displays infant temperature
Air temperature °C		Displays incubator air temperature
Set temperature		Illuminates when changing set temperature
Alarm indicators		High temp, Power fail, Sensor fault, Heater temp, Air flow, Low DC
Battery Specifications⁴		
Incubator		1 battery standard (2nd optional)
Type		Vented rechargeable, 12 Vdc, 24 AH gel-type battery (lead acid)
Battery rating		Incubator maintains a differential of 25 °C (77 °F) between ambient and set point for 90 minutes on 1 battery or 180 min. on 2 batteries at full heater power
Life expectancy		200 complete charge/discharge cycles minimum
Charge time		10 hours per battery from full discharge

TECHNICAL SPECIFICATIONS DRÄGER ISOLETTE® TI500 INCUBATOR

Safety Alarms

High temperature	Actuates if incubator air temp. $>39 \pm 0.5$ °C
Sensor (temperature)	Actuates if sensor fails
Heater temperature	Actuates if heater temp >77 °C (170 °F)
Power fail	Actuates if AC fails and no DC power present, and activates if unit switches from AC to DC current
Air flow	Actuates for fan failure
Low DC	Actuates if DC <10.5 Vdc, or external 28 Vdc falls below 25.5 Vdc nominal
Silence/reset	Silences the audible portion of alarms for 5 minutes, except Power fail. Resets Sensor & High Temp alarms after 100% conditions corrected. Resets intermittent power alert if unit switches from AC to DC current

Environmental

Storage temperature	-40 °C to 70 °C ambient
Operating range	Sea level to 3 km (10,000 ft.) non-pressurized environment. Sea level to 12 km (40,000 ft.)-pressurized environment

Relative Humidity

Operating range	0% to 95% RH, non-condensing
-----------------	------------------------------

Electrical

AC power requirements	110/120 V, 50/60/400 Hz – 220/240 V, 50/60/400 Hz
DC power requirements	11–13 V, 200 W (max) – 26–30 V, 200 W (max)
Observation lamp	35 footcandles – 4 inches above mattress 376 lux – 10 cm above mattress

¹ Weight includes one battery

² Humidity pad prevents spills

³ In ambients of 50 dBA or less

⁴ TI500 will maintain a differential of 25 °C (77 °F) between ambient and Set point for 90 minutes (one battery) or 3 hours (two batteries).

At differentials <25 °C (<77 °F), the TI500 maintains temperatures for longer periods

Not all products, features, or services are for sale in all countries.

Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany

www.draeger.com

Manufacturer:

Draeger Medical Systems, Inc.
3135 Quarry Road
Telford, PA 18969-1042, USA

Locate your Regional Sales Representative at:
www.draeger.com/contact



REGION DACH

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION EUROPE

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Singapore Pte. Ltd.
25 International Business Park
#04-20/21 German Centre
Singapore 609916
Tel +65 6308 9400
Fax +65 6308 9401
asia.pacific@draeger.com

REGION CENTRAL

AND SOUTH AMERICA
Dräger Panama S. de R.L.
Complejo Business Park,
V tower, 10th floor
Panama City
Tel +507 377-9100
Fax +507 377-9130
contactcsa@draeger.com

REGION NORTH AMERICA

Dräger, Inc.
3135 Quarry Road
Telford, PA 18969
Tel +1 800 4DRÄGER
(+1 800 437 2437)
Fax +1 215 723 5935
info.usa@draeger.com