



Manufactured in France

1 temperature cabinet

Large size

Premium Pack

Ideal for the conservation of wine on the short, medium and long term.

## Technical Specifications

Equipment  
**Standard shelf** 



Sliding shelf  
ACMS  
12 bottles



Storage shelf  
AXUH  
77 bottles

### Capacity

182 bottles\*

### Temperature

- Default setup temperature: 12°C / 54°F
- Temperature setting range from 6/ 43°F à 18°C/64°F

### Design

- 2 door options: glass with black frame or solid with black frame
- With or without handle\*\*
- Stainless steel tube handle
- Central lock
- Black control panel
- White interior lighting: 2 leds (ON/OFF)
- LED screen with touch-sensitive keys
- White screen display

### Accessories

- 14 ACMS shelves
- 1 EuroCave keyring
- Optional: set of 20 black aluminium plates + 1 erasable felt-tip marker Ref : ID20-STYLO

### Equipment

- Charcoal filter
- Clay ball humidity cassette
- Air circulation fan
- 2 adjustable feet at the front
- Condensate drip tray at the back

### Regulation

- Electronic regulation
- Display of the real temperature inside the cabinet
- Hygrometry display
- Visual alarms in case of dysfunction (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm)
- Automatic defrost

### Technologies

- Cold production:** Mixed air / Compressor R600a gas
- Cords:** CE/US/UK/JA/AU/CH/C6
- Heat production:** Resistance
- Heat release:** Automatic / Threshold: adjustable
- Inner material:** Aluminium
- Exterior coating material:** HPL panel (High pressure laminates)
- Insulation type:** Injected polyurethane foam (59mm)

\*Traditional Bordeaux format

\*\*Door with handle, not reversible

## General features

	Glass door	Solid door
Empty wine cabinet net weight (kg)	96	81
Equipped cabinet net weight (kg)	125	110
Gross weight packaged (kg)*	141	126
Dimensions H x W x D (mm)	1825 x 680 x 720***	1825 x 680 x 720***
Dimensions packaged (mm)	1950 x 720 x 760	1950 x 720 x 760
Colour	Nero - RAL 9005	Nero - RAL 9005

\*\*\*Incl. the separator at the back/ 690 mm without separator. The dimensions do not include the handle.

## Energy efficiency & Consumption

Cords	230V-50Hz (R600a)		115V-60Hz (R600a)	
	Solid	Glass	Solid	Glass
Type of door	Solid	Glass	Solid	Glass
Energy efficiency class	F	G	/	/
Annual energy consumption AEC (Kwh/year)	132	190	172	212
Sound emission (dB(A))	37	37	38	38
Sound emission Class	C	C	/	/
Ambient operating temperature (°C/°F)	0-35°C / 32-95°F	0-30°C / 32-86°F	0-35°C / 32-95°F	0-30°C / 32-86°F

La Premiere, in a few words...

## The fundamental by EuroCave.

The Première wine cabinet is designed for multiple uses. Concealed beneath its bold lines lies all the brand's expertise. Take your first steps into the world of EuroCave.

