



**RHINO**  
ANTI-FATIGUE MATS

# Comfort ☆ Craft®

## DATA & SPEC SHEETS

**Unmatched Safety Features:** Molded bevel edges - They will never curl up, eliminating trip hazards.

**Highest Quality:** Comfort Craft mats are rated first in comfort and durability due to the use of a premium Polyurethane compound with absolutely no fillers used in manufacturing.

**The Express Advantage:** Chemical and UV exposure will not affect the state of the top surface of the mat - No curling up - no swelling - no expanding.

The closed-cell/non-porous surface allows for wash down and cleaning. In case washing is necessary, wash surface with soap water (pH range 2 - 95.). Anti-static properties assure easy clean up.

### Limited Warranty:

Comfort Craft mats are conditionally warranted against normal home usage for a period of 5 years after date of purchase to the original owner.

Please forward the information to Ranco Industries, Inc. e-mail or regular mail care of:

Ranco Industries, Inc.

3421 Rusk

Houston, TX 77003

Attn: Warranties

info@rhinomats.com

SPEC DATA			CHEMICAL RESISTANCE		
Material		Integral Skin Polyurethane Foam	<b>TYPE</b>	<b>TOP</b>	<b>BACK</b>
			Weak Acid	Good	Fair
			Strong Acid	Fair	Poor
Top Surface		Domed	Weak Alkalis	Good	Fair
			Strong Alkalis	Fair	Poor
Size		24" x 36" / 6 lbs. 30" x 36" / 8 lbs.	Organic Solvents	Poor	Fair
			Alcohols	Fair	Fair
Thickness		.750"	Hydrocarbons	Excellent	Fair
			Water	Excellent	Fair
Density	ISO 2781	400 kg/m <sup>3</sup> +/-10%	UV Radiation	Good	Poor
Hardness	DIN 53505	37-54 Sh A	<b>STORING AND PACKAGING</b>		
Surface Durability	DIN 4649 taset equip. with 2,5N load	30 m	CC mats should be stored or inventoried flat. Mats rolled and boxed should be inventoried this way for short periods of time.		
Fire test	DIN 4102 Part 1/ section 6.1	Flame Retardant	Roll the mat with top surface to the outside - failure to roll the mat correctly may result in damage to the mat and will not be covered under warranty.		
Warranty		5 years			