Sikafloor®-304 W Part A



Version Revision Date: SDS Number: 1.2 01/23/2017 000000604358

SECTION 1. IDENTIFICATION

Product name Sikafloor®-304 W Part A

Manufacturer or supplier's details

: Sika Canada Inc. Company name

601, avenue Delmar

Pointe-Claire, QC H9R 4A9

Canada www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

Health and Safety Services's : ehs@ca.sika.com

e-mail address

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

Supplemental information

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

No hazardous ingredients

SECTION 4. FIRST AID MEASURES

Sikafloor®-304 W Part A



Version **Revision Date:** SDS Number: 1.2 01/23/2017 000000604358

General advice : No hazards which require special first aid measures.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

: No known significant effects or hazards.

See Section 11 for more detailed information on health effects

and symptoms.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

: Collect contaminated fire extinguishing water separately. This Further information

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Environmental precautions : Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for

containment and cleaning up

: Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling : For personal protection see section 8.

No special handling advice required.

Follow standard hygiene measures when handling chemical

Sikafloor®-304 W Part A



 Version
 Revision Date:
 SDS Number:

 1.2
 01/23/2017
 000000604358

products.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Store in accordance with local regulations.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

ed or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Sikafloor®-304 W Part A



 Version
 Revision Date:
 SDS Number:

 1.2
 01/23/2017
 000000604358

Appearance : liquid

Color : off-white

Odor : characteristic

Odor Threshold : No data available

pH : Not applicable

Melting point/range / Freezing

ooin

: No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : 23 hpa (17 mmHg)

Relative vapor density : No data available

Density : ca. 1.05 g/cm3 (20 °C (68 °F) ())

Solubility(ies)

Water solubility : partly soluble

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 7 mm2/s (40 °C)

Explosive properties : No data available

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Sikafloor®-304 W Part A



 Version
 Revision Date:
 SDS Number:

 1.2
 01/23/2017
 000000604358

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

: Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC Not applicable

NTP Not applicable

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Sikafloor®-304 W Part A



 Version
 Revision Date:
 SDS Number:

 1.2
 01/23/2017
 000000604358

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

Domestic regulation

TDG (road/train)

Not dangerous goods

International Regulations

IATA-DGR

Not dangerous goods

IMDG-Code

Not dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

Canadian PBT Chemicals : This product contains the following components on the DSL

that are classified as Persistent, Bioaccumulative and/or Toxic

(PBT) under CEPA:

octamethylcyclotetrasiloxane

Canadian lists

No substances are subject to a Significant New Activity Notification.

Sikafloor®-304 W Part A



 Version
 Revision Date:
 SDS Number:

 1.2
 01/23/2017
 000000604358

SECTION 16. OTHER INFORMATION

Revision Date : 01/23/2017

Prepared by : R & D of Sika Canada Inc.

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Full text of other abbreviations

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service
DNEL Derived no-effect level

EC50 Half maximal effective concentration GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships, 1973

as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic
PNEC Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

CA / Z8

Sikafloor®-304 W/305 W Part B



Version **Revision Date:** SDS Number: 1.1 01/16/2017 000000604186

SECTION 1. IDENTIFICATION

Product name Sikafloor®-304 W/305 W Part B

Manufacturer or supplier's details

Sika Canada Inc. Company name

601, avenue Delmar

Pointe-Claire, QC H9R 4A9

Canada www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax (514) 694-2792

Health and Safety Services's : ehs@ca.sika.com

e-mail address

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin irritation : Category 2

Serious eye damage : Category 1

Respiratory sensitization : Category 1

Skin sensitization : Category 1

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing diffi-

culties if inhaled.

Sikafloor®-304 W/305 W Part B



Version **Revision Date:** SDS Number: 1.1 01/16/2017 000000604186

Precautionary Statements

: Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves/ eye protection/ face protection. P284 In case of inadequate ventilation wear respiratory protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/doctor.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

Supplemental information

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Aliphatic polyisocyanate	28182-81-2	>= 90 - <= 100
polyethyleneglycol tridecyl ether phosphate (Average EO = 3 - 10 mol)	9046-01-9	>= 2 - < 5
N,N-dimethylcyclohexanamine	98-94-2	>= 1 -< 2
hexamethylene-di-isocyanate	822-06-0	>= 0 - < 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

Sikafloor®-304 W/305 W Part B



Version **Revision Date:** SDS Number: 1.1 01/16/2017 000000604186

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

: Take off contaminated clothing and shoes immediately. In case of skin contact

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

: Small amounts splashed into eyes can cause irreversible tis-In case of eye contact

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

: irritant effects sensitizing effects Asthmatic appearance Allergic reactions

Excessive lachrymation

Ervthema **Dermatitis**

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

: Collect contaminated fire extinguishing water separately. This **Further information**

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Sikafloor®-304 W/305 W Part B



 Version
 Revision Date:
 SDS Number:

 1.1
 01/16/2017
 000000604186

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

: Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage

: Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aliphatic polyisocyanate	28182-81-2	TWA	0.005 ppm	CA ON OEL
		С	0.02 ppm	CA ON OEL
N,N-dimethylcyclohexanamine	98-94-2	STEL	5 ppm 26 mg/m3	CA ON OEL

Sikafloor®-304 W/305 W Part B



 Version
 Revision Date:
 SDS Number:

 1.1
 01/16/2017
 000000604186

hexamethylene-di-isocyanate	822-06-0	TWA	0.005 ppm	CA AB OEL
			0.03 mg/m3	
		TWA	0.005 ppm	CA BC OEL
		С	0.01 ppm	CA BC OEL
		TWAEV	0.005 ppm	CA QC OEL
			0.034 mg/m3	
		TWA	0.005 ppm	CA ON OEL
		С	0.02 ppm	CA ON OEL
		TWA	0.005 ppm	ACGIH

Biological occupational exposure limits

Ingredients	CAS-No.	Control	Biological	Sam-	Permissible	Basis
		parameters	specimen	pling	concentra-	
				time	tion	
hexamethylene-di- isocyanate	822-06-0	1,6- Hexameth- ylene dia- mine	Urine	End of shift	15 μg/g creatinine	ACGIH BEI

Engineering measures

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Sikafloor®-304 W/305 W Part B



 Version
 Revision Date:
 SDS Number:

 1.1
 01/16/2017
 000000604186

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colorless

Odor : odorless

Odor Threshold : No data available

pH : Not applicable

Melting point/range / Freezing

point

: No data available

Boiling point/boiling range : > 150 °C (> 302 °F)

Flash point : 100 °C (212 °F)

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : 0.01 hpa (0.01 mmHg)

Relative vapor density : No data available

Density : ca. 1.13 g/cm3 (20 °C (68 °F) ())

Solubility(ies)

Water solubility : partly soluble

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 7 mm2/s (40 °C)

Sikafloor®-304 W/305 W Part B



 Version
 Revision Date:
 SDS Number:

 1.1
 01/16/2017
 000000604186

Explosive properties : No data available

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

: Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 23.94 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Ingredients:

N,N-dimethylcyclohexanamine:

Acute inhalation toxicity : LC50 (Rat): 4.45 mg/l

Exposure time: 4 h
Test atmosphere: vapor

hexamethylene-di-isocyanate:

Acute oral toxicity : LD50 Oral (Rat): 746 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.124 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rat): > 7,000 mg/kg

Sikafloor®-304 W/305 W Part B



 Version
 Revision Date:
 SDS Number:

 1.1
 01/16/2017
 000000604186

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: May cause allergy or asthma symptoms or breathing difficulties if in-

haled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC Not applicable

NTP Not applicable

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information

: Do not empty into drains; dispose of this material and its container in a safe way.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

8 / 10

Sikafloor®-304 W/305 W Part B



 Version
 Revision Date:
 SDS Number:

 1.1
 01/16/2017
 000000604186

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

Domestic regulation

TDG (road/train)

Not dangerous goods

International Regulations

IATA-DGR

Not dangerous goods

IMDG-Code

Not dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Revision Date : 01/16/2017

Prepared by : R & D of Sika Canada Inc.

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

Sikafloor®-304 W/305 W Part B



 Version
 Revision Date:
 SDS Number:

 1.1
 01/16/2017
 000000604186

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Full text of other abbreviations

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service
DNEL Derived no-effect level

EC50 Half maximal effective concentration

GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships, 1973

as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

CA / Z8