

## ⚠ WARNINGS AND CAUTIONS

- Make sure **POWER** is **COMPLETELY OFF** at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all times during this installation
- Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

### Please Note:

- When mounting on a sloped ceiling, install canopy with swivel facing along the slope of the ceiling to avoid damage to swivel (See Illustration 1).
- 120V input

## NOTICE

- The important safeguards and instructions outlined in this sheet cannot cover all possible conditions and situations that may occur. It must be understood that caution and certain care factors must be followed. These instructions are provided for your safety and we highly recommend that a licensed, trained electrician install this unit.
- This fixture is designed to be mounted on a correctly installed standard round or octagon box OR through a wiring box with a plaster frame. The box must be securely mounted to the structure of the building. The crossbar and hardware supplied should be used, directly mounting the fixture to the outlet box may make it impossible to correctly align the fixture.

## ASSEMBLY INSTRUCTIONS

### Step 1

Remove fixture from its original package.

### Step 2

Separate mounting plate (1c) from canopy (2a) by removing canopy screws (2b). Attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1e) in hardware package.

**Important: This fixture must be mounted independently from junction box, additional means of support is required.**

### Step 3

Secure mounting plate (1c) to mounting surface with anchors (1f) and screws (1g). Attach swivel (2e) to canopy (2a) with tooth washer and nut (4b).

### Step 4

Determine hanging height of fixture by securing rods (2d) to swivel (2e) and fixture (3a) after feeding fixture wires through rods.

### Step 5

Attach safety hooks (4a) onto mounting plate (1c).

### Step 6

Make proper electrical connections (**black to hot "L", white to neutral "N", ground to "GND"**) with wire nuts (1b) provided in hardware package.

### Step 7

Attach canopy (2a) to mounting plate (1c) with canopy screws (2b).

### Step 8

Install the recommended lamp (3b) (not provided) (referred on the socket label for maximum wattage and type) to fixture socket. Attach fixture glass (3c) to fixture (3a).

You are now ready to enjoy your fixture.

