1206008AST



Design By

BJARKE INGELS GROUP

Collection ==

Design

_	$\overline{}$
ւան	(IP20)

Colors & Finishes —

1
White

Specifications ———

Delivered lumens	6304lm
Light output ratio	114.6lm/W
Power consumption	55W
Led type	48.8W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V
Input Voltage	120-277V
Driver	N/A


Materials =

- Illuminated tubes in opaque injection molded PMMA resin
- 6 modules assembled
- 360° light emission
- Aluminum frame suspended by steel cables

Features & Accessories =

- Suitable for damp locations
- Driver is compatible to both 2-wire dimming and 0-10V dimming options

Dimensions ===



Ligh

Direc

Packaging =

1 x 43" x 110-5/16" x 7-9/16" / 21.16 lbs - 109 cm x 280 cm x 19 cm / 9.6 kg

ÿ2″ ÿ5cm €	min. 50 cm - max. 150 cm Extended length min. 19 ³⁴ " - max. 216 12" min. 50 cm - max. 550 cm		
	в 35 ^{лив*} в 90 cm		
nt distribution —		Luminaire weight	-
ct/Indirect		13.23 lbs / 6 kg	

Warranty -

