1992068A



Design By	
Ernesto Gismondi	

Collection

Design

ED	ը (Մ <u>ի</u> աչ	(P20)

Specifications	
Delivered lumens	2857.48lm
Light output ratio	71.44lm/W
Power consumption	41W
Led type	35W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V
Input Voltage	120-277V
Driver	EFORE - 1 x RCL050-1050A

Colors & Finishes

Transparent (Diffuser)

Bronze (Rim & Canopy)


Materials =

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA

Features & Accessories

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on
- The dimming range of the driver can dim down to 1%
- Driver is compatible to both 2-wire dimming and 0-10V dimming options

Dimensions =



Packaging =

1 Box

1 x 45-3/8" x 36-11/16" x 3-5/8" / 16.8 lbs - 115 cm x 93 cm x 9 cm / 7.62 kg

Light distribution —

Direct

Luminaire weight -

8.38 lbs / 3.8 kg

Warranty =

5 year limited warranty