

Design By -

BJARKE INGELS GROUP

Collection =

Design



Colors & Finishes =

Dicroic gradient (diffuser)

Polished Aluminum (canopy)

Materials =

- Aluminum canopy
- Blown glass diffuser
- Dichroic finishes made with an innovative and sustainable metal vacuum deposition process

Specifications —


Delivered lumens	495lm
Light output ratio	50lm/W
Power consumption	10W
Led type	8.2W C.O.B.*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 0-10V / Dimmable 2-Wire**
Input Voltage	120-277V
Driver	EFORE - 1 x RCL010-250A

^{*}Integrated light source **2-wire dimming at 120VAC only

Features & Accessories =

• Integrated driver dual-mode dimming, 2-wire and 0-10V dimming options

Dimensions =



Light distribution =

Diffused

Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

Packaging =

1 Box

1 x 13-1/2" x 13-1/2" x 15-13/16" / 8.38 lbs - 34 cm x 34 cm x 40 cm / 3.8 kg

Luminaire weight =

5.73 lbs / 2.6 kg

Warranty =

5 year limited warranty

