ASCOLI FLOOR

astro

GENERAL

LOCATION: Interior
CLASS: cULus (Class 1)

LOCATION RATING: Dry
DRIVER REQUIRED: Mains 120V

INSTALLATION ORIENTATION: FITTING METHOD: -

 MAIN MATERIAL:
 Metal - Mild Steel

 DIMENSIONS (mm):
 H: 1227 W: 200 D: 286

 DIMENSIONS (inch):
 H: 48.31 W: 7.87 D: 11.26

CUT OUT HOLE (mm/inch):
RECESS DEPTH (mm/inch):
FIRE RATING: -

CABLE LENGTH (mm/inch): 3000/118.11

GROSS WEIGHT (lb): 14.7

ADA COMPLIANT: Yes - if installed in compliance with ADA 308, 309.3, 309.4

IC RATING:

LAMP

LIGHT SOURCE: GU10
WATTAGE: 20W Max

RECOMMENDED LAMP: 6W Max LED GU10

LAMP INCLUDED: No
MAXIMUM LAMP LENGTH (mm/inch): 57/2.24

 LUMINOUS FLUX (Im):
 Lamp Dependent

 COLOUR TEMP (K):
 Lamp Dependent

 CRI (Ra):
 Lamp Dependent

 MACADAM ELLIPSE:
 Lamp Dependent

TILT ADJUSTABLE ANGLE (°): 90
ROTATION ADJUSTABLE ANGLE (°): 330

LIFETIME (hrs): Lamp Dependent BEAM ANGLE (°): Lamp Dependent

ELECTRICAL

SWITCHED: Yes

DIMMABLE: No

DIMMING METHOD:
SUPPLY FREQUENCY (Hz):
DRIVER/BALLAST VOLTAGE (V):
DRIVER LIFETIME (hrs): -

EFFICACY (Im/W): Lamp Dependent

ADDITIONAL INFORMATION:

SHADE INCLUDED: SHADE/DIFFUSER MATERIAL: SHADE/DIFFUSER FINISH F MARK: -







CODE: 1286113 FINISH: MATT NICKEL



CODE: 1286114 FINISH: MATT WHITE



CODE: 1286136 FINISH: MATT BLACK

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.





