ASCOLI SINGLE SWITCHED

astro

GENERAL

LOCATION: Interior

CLASS: cETLus (Class 1)

LOCATION RATING: Dry

DRIVER REQUIRED: Mains 120V
INSTALLATION ORIENTATION: Wall mount
FITTING METHOD: 4" Octagon Box
MAIN MATERIAL: Metal - Zinc

DIMENSIONS (mm): H: 110 W: 108 D: 130
DIMENSIONS (inch): H: 4.33 W: 4.25 D: 5.12

CUT OUT HOLE (mm/inch):

RECESS DEPTH (mm/inch):

FIRE RATING:

CABLE LENGTH (mm/inch):

GROSS WEIGHT (kg):

1.45

ADA COMPLIANT: Yes - if installed in compliance with ADA 307.2, 308, 309.3, 309.4

IC RATING:

LAMP

LIGHT SOURCE: GU10 WATTAGE: 50W

RECOMMENDED LAMP: 6W Max LED GU10

LAMP INCLUDED: No MAXIMUM LAMP LENGTH (mm/inch): 57

 LUMINOUS FLUX (Im):
 Lamp Dependent

 COLOUR TEMP (K):
 Lamp Dependent

 CRI (Ra):
 Lamp Dependent

MACADAM ELLIPSE: TILT ADJUSTABLE ANGLE (°): 90
ROTATION ADJUSTABLE ANGLE (°): 330

LIFETIME (hrs): Lamp Dependent BEAM ANGLE (°): Lamp Dependent

ELECTRICAL

SWITCHED: Yes

DIMMABLE: No

DIMMING METHOD:
SUPPLY FREQUENCY (Hz):
DRIVER/BALLAST VOLTAGE (V):
DRIVER LIFETIME (hrs): -

EFFICACY (Im/W): Lamp Dependent

ADDITIONAL INFORMATION:

SHADE INCLUDED: SHADE/DIFFUSER MATERIAL: SHADE/DIFFUSER FINISH -

F MARK: Suitable for mounting on flammable materials







CODE: 1286043 FINISH: BRONZE



CODE: 1286048 FINISH: MATT NICKEL



CODE: 1286121 FINISH: MATT BLACK

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED.
ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED
UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS,
AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY
RESFERVED.



Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.







