ENNA SURFACE USB

astro

GENERAL

LOCATION: Interior
CLASS: cULus (Class 1)

LOCATION RATING: Dry

DRIVER REQUIRED: Mains 120V

INSTALLATION ORIENTATION: Wall Mount - Vertical & Horizontal

FITTING METHOD: 3x2" Switch Box MAIN MATERIAL: Metal - Zinc

DIMENSIONS (mm): H: 255 W: 80 D: 141

DIMENSIONS (inch): H: 8.86 W: 3.15 D: 5.55

CUT OUT HOLE (mm/inch):

RECESS DEPTH (mm/inch):

FIRE RATING:

CABLE LENGTH (mm/inch):

GROSS WEIGHT (lb):

2.39

ADA COMPLIANT: Yes - if installed in compliance with ADA 307.2, 308, 309.3, 309.4

IC RATING: Non IC Rated

LAMP

LIGHT SOURCE: High Powered LED

WATTAGE: 3.2W

LAMP INCLUDED: Yes (Integral)

MAXIMUM LAMP LENGTH (mm/inch): LUMINOUS FLUX (Im): 131 COLOUR TEMP (K): 2700 CRI (Ra): 90 MACADAM ELLIPSE: 3-Step TILT ADJUSTABLE ANGLE (°): 90 ROTATION ADJUSTABLE ANGLE (°): 330 LIFETIME (hrs): 60000 BEAM ANGLE (°): 14.3

ELECTRICAL

SWITCHED: Yes
DIMMABLE: No
DIMMING METHOD: -

SUPPLY FREQUENCY (Hz): 50-60

DRIVER/BALLAST VOLTAGE (V): 100-240

DRIVER LIFETIME (hrs): 30000

EFFICACY (Im/W): 41

ADDITIONAL INFORMATION:

SHADE INCLUDED: SHADE/DIFFUSER MATERIAL: SHADE/DIFFUSER FINISH F MARK: -



CODE: 1058158 FINISH: MATT NICKEL



CODE: 1058162 FINISH: MATT BLACK



CODE: 1058163 FINISH: MATT WHITE



CODE: 1058164 FINISH: MATT GOLD



CODE: 1058188 FINISH: BRONZE

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.







