

Halftone 600

astro

General

Location:	Interior
Class:	cULus (Class 1)
Location Rating:	Dry
Driver Required:	Mains 120V
Installation Orientation:	Wall Mount
Fitting Method:	Included 1/2" Stub Mount & 4" Octagon Box
Main Material:	Metal - Mild Steel
Dimensions (mm):	D: 67.2 Ø: 600
Dimensions (inch):	D: 2.65 Ø: 23.62
Cut Out Hole (mm/inch):	-
Recess Depth (mm/inch):	-
Fire Rating:	-
Cable Length (mm/inch):	-
Gross Weight (lb):	13.76
Ada Compliant:	Yes
Ic Rating:	-

Lamp

Light Source:	LED Strip
Wattage:	14.4W
Lamp Included:	Yes (Integral)
Maximum Lamp Length (mm/inch):	-
Luminous Flux (lm):	247
Colour Temp (K):	2700
Cri (Ra):	80
Macadam Ellipse:	2610-2710K
Tilt Adjustable Angle (°):	-
Rotation Adjustable Angle (°):	-
Average Lifetime (hrs):	53000
Beam Angle (°):	-

Electrical

Switched:	No
Dimmable:	Yes
Dimming Method:	0-10V
Supply Frequency (Hz):	47/63
Driver/Ballast Voltage (V):	120-277
Driver Average Lifetime (hrs):	100000
Efficacy (lm/W):	17

Additional Information:

Shade Included:	-
Shade/Diffuser Material:	Polycarbonate
Shade/Diffuser Finish:	Clear
F Mark:	-



CODE: 1425006
FINISH: MATT WHITE

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Product Elevations

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

