

General

Location:	Interior
Class:	cULus (Class 2)
Location Rating:	Dry
Driver Required:	5V DC
Installation Orientation:	-
Fitting Method:	-
Main Material:	Metal - Aluminium
Dimensions (mm):	H: 264 Ø: 162
Dimensions (inch):	H: 10.39 Ø: 6.38
Cut Out Hole (mm/inch):	-
Recess Depth (mm/inch):	-
Fire Rating:	-
Cable Length (mm/inch):	-
Gross Weight (lb):	2.16
Ada Compliant:	Yes
Ic Rating:	-

Lamp

Light Source:	LED
Wattage:	2.6W
Lamp Included:	Yes (Integral)
Maximum Lamp Length (mm/inch):	-
Luminous Flux (lm):	214
Colour Temp (K):	2700
Cri (Ra):	90
Macadam Ellipse:	3-Step
Tilt Adjustable Angle (°):	-
Rotation Adjustable Angle (°):	-
Average Lifetime (hrs):	50000
Beam Angle (°):	-

Electrical

Switched:	Yes
Dimmable:	Yes
Dimming Method:	Integral Touch Dimmer
Supply Frequency (Hz):	-
Driver/Ballast Voltage (V):	5V DC
Driver Average Lifetime (hrs):	-
Efficacy (lm/W):	82

Additional Information:

Shade Included:	-
Shade/Diffuser Material:	Plastic
Shade/Diffuser Finish:	Frosted
F Mark:	-



CODE: 1468004
FINISH: MATT BLACK



CODE: 1468005
FINISH: MATT WHITE



CODE: 1468006
FINISH: LIGHT BRONZE

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under u.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

