MICRO RECESS SWITCHED

astro

GENERAL

LOCATION: Interior

CLASS: cETLus (Class 1)

LOCATION RATING: Damp
DRIVER REQUIRED: Mains 120V

INSTALLATION ORIENTATION: Wall Mount - Vertical FITTING METHOD: Included Junction Box MAIN MATERIAL: Metal - Mild Steel DIMENSIONS (mm): D: 97 Ø: 80 DIMENSIONS (inch): D: 3.82 Ø: 3.15 CUT OUT HOLE (mm/inch): Ø: 70/2¾" RECESS DEPTH (mm/inch): 55/2.17

FIRE RATING: CABLE LENGTH (mm/inch): GROSS WEIGHT (Ib): 0.98

ADA COMPLIANT: Yes - if installed in compliance with ADA 307.2, 308, 309.3, 309.4

IC RATING: IC Rated

LAMP

LIGHT SOURCE: High Power LED

WATTAGE: 3.2W

LAMP INCLUDED: Yes (Integral)

MAXIMUM LAMP LENGTH (mm/inch): LUMINOUS FLUX (Im): 196 COLOUR TEMP (K): 2700 CRI (Ra): 90 MACADAM ELLIPSE: 3-Step TILT ADJUSTABLE ANGLE (°): 90 ROTATION ADJUSTABLE ANGLE (°): 330 LIFETIME (hrs): 60000 BEAM ANGLE (°): 16

ELECTRICAL

SWITCHED: Yes
DIMMABLE: No
DIMMING METHOD: -

SUPPLY FREQUENCY (Hz): 50-60

DRIVER/BALLAST VOLTAGE (V): 100-277

DRIVER LIFETIME (hrs): 30000

EFFICACY (Im/W): 61

ADDITIONAL INFORMATION:

SHADE INCLUDED: -

SHADE/DIFFUSER MATERIAL: Polycarbonate

SHADE/DIFFUSER FINISH Black

F MARK: To Be Advised



CODE: 1407016 FINISH: MATT WHITE



CODE: 1407017 FINISH: MATT BLACK



CODE: 1407018 FINISH: MATT NICKEL



CODE: 1407019 FINISH: BRONZE



CODE: 1407020 FINISH: MATT GOLD

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.



Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.









