PENDANT SUSPENSION KIT 3

astro

GENERAL

LOCATION: Interior
CLASS: cULus (Class 1)

LOCATION RATING: Dry

DRIVER REQUIRED: Mains 120V

INSTALLATION ORIENTATION: Ceiling Mount

FITTING METHOD: 4" Octagon Box

MAIN MATERIAL: Metal - Mild Steel

DIMENSIONS (mm): H: 2584 max W: 110 D: 335 max
DIMENSIONS (inch): H: 101.7 max W: 4.33 D: 13.19

CUT OUT HOLE (mm/inch): RECESS DEPTH (mm/inch): FIRE RATING: -

CABLE LENGTH (mm/inch): 2500/98.43

GROSS WEIGHT (lb): 2.63

ADA COMPLIANT: Yes - if installed in compliance

with ADA 307.4

IC RATING: -

LAMP

LIGHT SOURCE: LED E26/Medium

WATTAGE: 12W Max

RECOMMENDED LAMP: 12W Max LED E26/Medium

LAMP INCLUDED: No MAXIMUM LAMP LENGTH (mm/inch): -

 LUMINOUS FLUX (Im):
 Lamp Dependent

 COLOUR TEMP (K):
 Lamp Dependent

 CRI (Ra):
 Lamp Dependent

 MACADAM ELLIPSE:
 Lamp Dependent

TILT ADJUSTABLE ANGLE (°): ROTATION ADJUSTABLE ANGLE (°): -

LIFETIME (hrs): Lamp Dependent BEAM ANGLE (°): Lamp Dependent

ELECTRICAL

SWITCHED: No DIMMABLE: Yes

DIMMING METHOD: Lamp Dependent

SUPPLY FREQUENCY (Hz): DRIVER/BALLAST VOLTAGE (V): DRIVER LIFETIME (hrs): -

EFFICACY (Im/W): Lamp Dependent

ADDITIONAL INFORMATION:

SHADE INCLUDED: Shade Sold Separately

SHADE/DIFFUSER MATERIAL: SHADE/DIFFUSER FINISH F MARK: -







CODE: 1184018 FINISH: BRONZE

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.







