

1. Overall dimensions of the lamp.

2. Only if fluorescent lamp is used.
Unscrew the body (B) from the base (C) and pull up.
Fit the bulbs in the bulb holder.

3. Counterweight filling (optional): To augment the lamp's stability, the Inn Side offers users the ability to fill the counterweight with water or sand. To do this, unscrew the counterweight (A) from the base (C) and pull up. Unscrew the cap (D) from the counterweight (A) using a coin, and fill the container with water or sand. Replace the cap and rescrew the body on.


MAINTENANCE TIPS

The INN SIDE wooden lamp is weather-treated. However, to protect and preserve the wood's characteristics, we recommend that it be treated yearly with CETOL WF771, by the brand SIKKENS.

Consumer information:

- Lamps without the IP mark are classed as IP20 and are designed for general interior use, except wet areas (bathrooms, etc.)
- Lamps with the IP mark are designed for exterior use and in wet areas. (E.g. IP54)
- They offer guaranteed protection to people and animals against electrical discharge:
 - Class I: through single electrical insulation and an earthing conductor once correctly connected.
 - ◻ • Class II: through double electrical insulation.
 - ◊ • Class III: these kinds of lamps should be connected at very low voltage levels (generally 12V); therefore there is no risk.
- ▽ • Lamps with this symbol, or without any symbols, can be mounted directly onto normally inflammable surfaces.
- ⊗ • Lamps with this symbol cannot be mounted directly onto normally inflammable surfaces.
 - The safety of this lamp is guaranteed by using a maximum wattage bulb that does not exceed the figure displayed visibly on the lamp.
- ♻️ • The product cannot be treated like conventional domestic waste; it must be taken to the corresponding recycling point for electrical and electronic equipment.

Assembly instructions



B.LUX S.A.

Pol. Ind. Okamika, pab. 1
48289 Gizaburuaga (Bizkaia) Spain
T. (+34) 94 682 72 72
F. (+34) 94 682 49 02
info@grupoblux.com
www.grupoblux.com