




Calx 19, walnut, brushed brass

Calx 19 pendant



Dimensions: 13" x 13", 12.75"
Materials: wood, metal, polymer
Product weight: 7 lb
Suitable for a sloped ceiling

Integrated LED Specifications
Light output: 1250 Lumens (source)
Light color*: 2700 K or 3500 K
Color accuracy: 90+ CRI
Power usage: 13 W
Dimmable (see driver below)
White (CM-060) extended-profile round canopy with white braided cord and steel cable included
Canopy dimensions: 5"Ø, 2"
Canopy required to house LED driver (3.3" x 1.6" x 1.0")
See below for more canopy information
72" drop length, field adjustable

Medium Base Specifications
Lamping: 1x E26 base, type A lamp, 60 W max
Bulb not included
Input voltage: 250 V AC max
White (CM-060) low-profile round canopy with white SPT cord and steel cable included
Canopy dimensions: 5"Ø, 0.3"
72" drop length, field adjustable
Suitable for a sloped ceiling
Wood grain will vary
Specifications subject to change



brushed brass
(CM-047)



brushed aluminum
(CM-012)



brushed rose gold
(CM-046)





walnut
(CM-055)



dark stained walnut
(CM-056)



white washed oak
(CM-095)



Calx 19 E26
low-profile round
canopy with white SPT
cord with steel cable



Calx 19 Integrated LED
extended-profile round
canopy braided cord
with steel cable



The Calx is an example of modern design where the methods and the materials themselves are integral to its very conception, aligning form and function, which creates a synergy that is evident. The fixture ultimately forms a square aperture but enjoys a beautifully simple faceted structure.

Nick Sheridan,
Designer

MATERIAL & FINISH OPTIONS

Calx 19 part # 06-200-19

Metal Finish

brushed aluminum (CM-012) A
brushed rose gold (CM-046) G
brushed brass (CM-047) R

Wood Finish

walnut (CM-055) W
dark stained walnut (CM-056) D
white washed oak (CM-095) O

Lamping*

2700 K LED 27
3500 K LED 35
medium base E26 socket MB

Driver (LED version only)

AC Input Voltage Range: 120-277 V
120 V input: TRIAC, ELV & 0-10 V dimmable
240 & 277 V input: only 0-10 V dimmable

Includes

frosted polymer diffuser (CM-057)

*Available in 3000K, 4000K and other color temperatures upon request

