



FU186244 Anodized Champagne

## **Coordinates Suspension 2**

Designed by Michael Anastassiades, 2020



55W - 2960lm - 2700K - CRI> 95

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

#### Main specifications

EAN	8059607034316
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	55
System flux (Im)	2960

### Physical

Color	Anodized Champagne
Length (in)	69.37
Cord length (in)	94
Net weight (lb)	5.95
Package volume (in)	1748.21
IP internal	20







#### Download

Mounting instructions



#### Photometric Files

ULD



#### **Technical Drawings**

3D











#### Photometric

Lighting type	Total
Light distribution	Asymmetric
CCT (K)	2700
CRI>	95

#### Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

# Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F** 



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional



O1. Power supply kit for RF0410500
 Arrangements small &
 Noctambule

O2. Led dimmer kit RF0410300

https://professional.flos.com/en-US/us/product/coordinates-suspension-2-fu186244/

FU186244





RF0410500

Power supply kit for Arrangements small & Noctambule RF0410300

Led dimmer kit