

# FLOS

FU185044 Anodized Champagne

## Coordinates Suspension 3

Designed by Michael Anastassiades, 2020



71W - 3850lm - 2700K - CRI> 95

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications


EAN	8059607034330
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	71
System flux (lm)	3850

### Physical


Color	Anodized Champagne
Length (in)	30.79
Cord length (in)	94
Net weight (lb)	7.06
Package volume (in)	2160.85
IP internal	20



### Download

[Mounting instructions](#)  PDF

### Photometric Files

[ULD](#)  ZIP

### Technical Drawings

[3D](#)  ZIP



## Photometric

Lighting type	Total
Light distribution	Asymmetric
CCT (K)	2700
CRI>	95

## Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
LED voltage Vf (Vdc)	null
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

## Spare Parts



- |     |  |           |
|-----|--|-----------|
| 01. | Power supply kit for<br>Arrangements small &<br>Noctambule | RF0410500 |
| 02. | Led dimmer kit   | RF0410300 |



RF0410500

Power supply kit for  
Arrangements small &  
Noctambule



RF0410300

Led dimmer kit