

MODEL NAME **DRR6-CC NOTCH**
6-Inch Regressed Panel Light


The Notch series of regressed downlights is characterized by a deep-set LED position which greatly reduces glare, neatly packaged in a price-conscious solution to general lighting.



PROJECT: _____ **TYPE:** _____

DATE: _____ **QTY:** _____

NOTES:




QUICK SPECS

SIZE	WATTS	DELIVERED LUMENS*	COLOR °T 5CCT	CRI	VOLTAGE	BEAM ANGLE	FINISH
6"	14W	1000lm	2700K 3000K 3500K 4000K 5000K	90	120V	100°	○ White

*Lumen output measured at 3000K

LIGHT DISTRIBUTION



CONSTRUCTION	Lens Frosted	Type of optics Acrylic	Type of LED SMD
	Lens material Plastic	Housing material Cast aluminum	Cut hole size 6-1/2"

RATINGS	Placement Indoor/Outdoor	Lifespan 50,000 hrs.	FT rating FT6
	Location Wet	Certifications ETL, FCC, ICES, ES IC, ASTM E283-04, T24	Operating temperature -20° to 40° C

WHAT'S IN THE BOX

- LED recessed fixture
- Junction box
- Push-in wire connectors
- Mounting hardware
- Instruction sheet

ACCESSORIES

- [RFP-UNI](#) Universal Drilling Plate
- [DRR6-TRIM-BK](#) Panel Trim in Black
- [DRR6-TRIM-SBA](#) Panel Trim in Sandblasted Aluminum
- [RFP-46](#) Drilling Plate

ADAPTERS

- [REC-EXT108](#) 108" extension cord for recessed fixtures
- [REC-EXT230](#) 230" extension cord for recessed fixtures



**ELECTRICAL
DETAILS**

Input voltage
108-135V

Output current
327mA

Power factor
98%

Driver type
Constant current

Output voltage
35V

LED model #
2835

**THD harmonic
distortion**
<30%

Binning type
3,6 SDCM

FEATURES

Every fixture includes a junction box with an integrated driver

Superior LED performance and lifespan

Minimal heat emission

Switch-selectable CCT:
2700K/ 3000 K/ 3500 K/
4000 K/ 5000 K

Frosted lens

Can be daisy chained

Smooth 360° wide spread

Back-lit technology

WARRANTY

DALS offers a 5-year warranty from the date of purchase which covers repairs or replacement of defective parts of the housing, optics, and electronics. To contact DALS customer service call 1-877-430-1818 or send an e-mail to info@dals.com.

RECOMMENDED DIMMER LIST*

BRAND	MODEL #	DIMMER SPECS	GRADE	DIMMING RANGE (%)	MAX LOAD
Lutron	DVELV-300P-WH	300W electronic low voltage dimmer	Compatible	Min: 5 / Max: 98	20
Lutron	MA-PRO-WH	ELV, 250W LED/CFL	Compatible	Min: 0 / Max: 99	16
Lutron	Caseta PD-5NE-WH-C	ELV, LED—up to 250 W	Compatible	Min: 1 / Max: 99	16
Control 4	C4-APD120-WH	ELV, 120W LED	Compatible	Min: 0 / Max: 100	8

* Minimal buzzing noise may occur with some dimmers