SwivLED





To swivel or not to swivel is the question. With an ultra-slim profile, our LED strips can be fixed or flexible. Because you have both types of brackets included with each model, the choice is yours.



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
SWIVLED12	13.125"	3.2 W	270 lm	300 lm	80	3000 K	12 V
SWIVLED12-4K	13.125"	3.1 W	275 lm	300 lm	80	4000 K	12 V
SWIVLEDHP	13.125"	4.5 W	420 lm	600 lm	80	3000 K	12 V
SWIVLEDHP-4K	13.125"	4.5 W	440 lm	600 lm	80	4000 K	12 V

Specifications

Over 50,000 hours of service life 10" (25 cm) power cord included Smooth linear wide spread Minimal heat emission

No UV light emission

Multiple fixtures can be linked together (Up to 8x SWIVLED in series

Up to 4x SWIVLEDHP in series)

Refer to website for dimmer compatibility 5-year warranty

Note

Plug-in or hard-wired power supply required for installation. Sold separately.

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALS representative for more information.

Power supplies: plug-in

ETR-LED10WPI

12VDC/10W class 2 LED driver

ETR-LED24WPI

12VDC/24W class 2 LED driver

Power supplies: hard-wired

BT06DIM-IC

6W dimmable LED hardwire driver

BT12DIM-IC

12W dimmable LED hardwire driver

BT24DIM-IC

24W dimmable LED hardwire driver

BT36DIM

36W dimmable LED hardwire driver

48W dimmable LED hardwire driver

Accessories

SWIVLED-EXT-10

10" extension cord

SWIVLED-EXT-36

36" extension cord

SWIVLED-EXT-60

60" interconnection harness

SWIVLEDACC-45VCLIP

45° clips

SWIVLED-CC10-OUTPUT

10" output connector

Finish

SBA Sandblasted aluminum

Order example

SWIVLEDHP

SwivLED high-power strip with a 4.5W LED array, with 420 lumens at 3000K in a sandblasted aluminum finish

SWIVLED_

*Add 12.5" for each additional unit



