

# IN THE TUBE 120 - 1300

by Dominique Perrault & Gaëlle Lauriot-Prévost



## TECHNICAL SHEET

North America standards

## FICHE TECHNIQUE

normes Nord Américaines




WALL & PENDANT LAMP APPLIQUE & SUSPENSION

|                   |   |
|-------------------|---|
| <b>Materials</b>  | <p>Tube: <b>borosilicate glass</b><br/>         Waterproof stopper: <b>black silicon and aluminium cast or transparent polycarbonate</b><br/>         Adjustable collar: <b>stainless steel</b><br/>         Removable mesh: <b>brass / stainless steel</b><br/>         Reflector: <b>aluminium and stainless steel</b><br/>         Fastenings: <b>stainless steel</b><br/>         Wire: <b>black rubber</b></p> |
| Matériaux         | <p>Tube: verre borosilicate<br/>         Bouchon étanche: silicone et fonte d'aluminium noirs ou polycarbonate transparent<br/>         Collier de fixation: acier inoxydable<br/>         Maille amovible: laiton/acier inoxydable<br/>         Réflecteur: aluminium et acier inoxydable<br/>         Visserie: acier inoxydable<br/>         Câble: caoutchouc noir</p>  |
| <b>Net weight</b> | <b>9 kg</b>   |
| Poids net         |   |
| <b>Use</b>        | <b>Indoor / outdoor / bathroom</b>  |
| Usage             | Intérieur / extérieur / salle de bain   |
| <b>Packaging</b>  | <b>63 x 14.56 x 13 in</b>   |
| Emballage         | 1600 x 370 x 330 mm   |
| <b>IP IP</b>      | <b>20</b><br><b>IP 64 on request / IP64 sur demande</b>   |
| <b>IK IK</b>      | <b>07</b>   |

|                             |   |
|-----------------------------|---|
| <b>Voltage</b>              | <b>110V</b>   |
| Tension                     |   |
| <b>Class</b>                | <b>1</b>  |
| Classe                      |   |
| <b>Watt</b>                 | <b>(6 x) 23W (LED ONLY)</b>                             |
| Watt                        |   |
| <b>Bulb type</b>            | <b>(6 x) E26 LED (Bulb not included)</b>                |
| Type d'ampoule              | (6 x) E26 LED (Ampoules non fournies)                   |
| <b>Lumens output</b>        | <b>1376,87 lm (indicative value)</b>                    |
| Lumens                      | 1376,87 lm (valeur indicative)                          |
| <b>Driver</b>               | <b>NA</b>   |
| Driver                      |   |
| <b>Wire</b>                 | <b>Black rubber, length : 118 in - Debrochable</b>      |
| Câble                       | Caoutchouc noir, longueur : 3 m - Débrochable           |
| <b>Accessories included</b> | <b>2 Adjustable collars + junction box are included</b> |
| Accessoires fournis         | 2 Colliers de fixations + boîtier de dérivation fournis |
| <b>Switch</b>               | <b>NA</b>   |
| Interrupteur                |   |
| <b>Plug</b>                 | <b>NA</b>   |
| Fiches                      |   |

### REFLECTOR RÉFLECTEUR



### MESH MAILLE



### STOPPER BOUCHON



# IN THE TUBE 120 - 1300

by Dominique Perrault & Gaëlle Lauriot-Prévost

## TECHNICAL SHEET North America standards

## FICHE TECHNIQUE normes Nord Américaines

### PHOTOMETRIC DATA

### DONNÉES PHOTOMÉTRIQUES

**Flux** **1376,87 lm**  
**(indicative value)**  
(valeur indicative)

**Tc** **NA**

**CRI** **NA**

**Tested lamp** **E26**  
Ampoule testée **Led filament**  
**7 W**  
**806 lumens**  
**2700 K**

