

IN THE TUBE 120 - 1300

by Dominique Perrault & Gaëlle Lauriot-Prévost



TECHNICAL SHEET

North America standards

FICHE TECHNIQUE

normes Nord Américaines




WALL & PENDANT LAMP APPLIQUE & SUSPENSION

| | |
|-------------------|---|
| Materials | <p>Tube: borosilicate glass Waterproof stopper: black silicon and aluminium cast or transparent polycarbonate Adjustable collar: stainless steel Removable mesh: brass / stainless steel Reflector: aluminium and stainless steel Fastenings: stainless steel Wire: black rubber</p> |
| Matériaux | <p>Tube: verre borosilicate Bouchon étanche: silicone et fonte d'aluminium noirs ou polycarbonate transparent Collier de fixation: acier inoxydable Maille amovible: laiton/acier inoxydable Réflecteur: aluminium et acier inoxydable Visserie: acier inoxydable Câble: caoutchouc noir</p> |
| Net weight | 9 kg |
| Poids net | |
| Use | Indoor / outdoor / bathroom |
| Usage | Intérieur / extérieur / salle de bain |
| Packaging | 63 x 14.56 x 13 in |
| Emballage | 1600 x 370 x 330 mm |
| IP IP | 20 |
| | IP 64 on request / IP64 sur demande |
| IK IK | 07 |

| | |
|-----------------------------|---|
| Voltage | 110V |
| Tension | |
| Class | 1 |
| Classe | |
| Watt | (6 x) 23W (LED ONLY) |
| Watt | |
| Bulb type | (6 x) E26 LED (Bulb not included) |
| Type d'ampoule | (6 x) E26 LED (Ampoules non fournies) |
| Lumens output | 1376,87 lm (indicative value) |
| Lumens | 1376,87 lm (valeur indicative) |
| Driver | NA |
| Driver | |
| Wire | Black rubber, length : 118 in - Debrochable |
| Câble | Caoutchouc noir, longueur : 3 m - Débrochable |
| Accessories included | 2 Adjustable collars + junction box are included |
| Accessoires fournis | 2 Colliers de fixations + boîtier de dérivation fournis |
| Switch | NA |
| Interrupteur | |
| Plug | NA |
| Fiches | |

REFLECTOR RÉFLECTEUR



MESH MAILLE



STOPPER BOUCHON



IN THE TUBE 120 - 1300

by Dominique Perrault & Gaëlle Lauriot-Prévost

TECHNICAL SHEET North America standards

FICHE TECHNIQUE normes Nord Américaines

PHOTOMETRIC DATA

DONNÉES PHOTOMÉTRIQUES

Flux **1376,87 lm**
(indicative value)
(valeur indicative)

Tc **NA**

CRI **NA**

Tested lamp **E26**
Ampoule testée **Led filament**
7 W
806 lumens
2700 K

