

INSTALLATION INSTRUCTION

533-LED Wall Sconce

WS-53318

dweLED

CAUTION: To prevent electrical shock, ensure electricity has been turned off at the circuit breaker before beginning.

- Read all instructions before installing.
- System is intended for installation by a licensed electrician in accordance with the National Electrical Code (NEC) and local regulations.
- When handling the fixture, do not apply pressure to the LEDs. Hold the fixture by the base only.
- Retain installation instructions for future maintenance reference.

WARNING: All parts must be used as indicated in these instructions. This product is designed for use only with the supplied parts and/or accessories designated for use by dweLED. Substitution of parts or accessories not designated for use with this product by dweLED could result in personal injury or property damage, and will void the warranty. Contact an authorized dealer or the manufacturer if any parts are damaged or missing.

MAINTENANCE NOTE: Coastal conditions may cause mineral and residue build-up on the fixture. We recommend that customers in coastal areas clean all external surfaces of the fixture once every two weeks with a wet cloth.


MISE EN GARDE: Pour éviter tout choc électrique, assurez-vous que le disjoncteur soit mis hors tension avant de commencer.

- Lisez toutes les instructions avant l'installation.
- Le système doit être installé par un électricien licencié conformément au code national de l'électricité (NEC), et également aux règlements locaux.
- Lors de la manipulation du luminaire, n'appuyez pas sur les LED. Tenez-le uniquement par la base.

ATTENTION: Toutes les pièces doivent être utilisées comme indiqué dans ces instructions. Ce produit est conçu pour être utilisé seulement avec les pièces et/ou accessoires fournis pour être utilisés avec les produits dweLED. Remplacer des pièces ou accessoires non conçus pour ce produit dweLED pourrait causer des dommages corporels ou matériels et pourrait également causer l'annulation de la garantie. Veuillez contacter un revendeur autorisé ou le fabricant si des pièces manquent ou sont endommagées.

NOTE D'ENTRETIEN: Les conditions côtières peut causer une accumulation de minéraux et de résidus sur le luminaire. Nous recommandons aux clients qui résident dans les zones côtières de nettoyer toutes les surfaces externes du luminaire une fois toutes les deux semaines avec un chiffon humide.


HARDWARE



Wire Connector
Qty: 3pcs+1 Extra



Mounting Screw
Qty:1 Extra



PREPARATION

1. Shut off the power at the circuit breaker and remove existing fixture, including the crossbar.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Be careful not to lose any small parts necessary for installation.

MOUNTING THE FIXTURE (Fig. 1)

3. Remove the mounting screw (B) from the fixture.
4. Set color temperature at this stage. The fixture can switch between three color temperatures (2700K, 3000K, 3500K), which can be adjusted to your preference using the 3CCT switch (Fig. 3) mounted on the mounting back plate.

5. Secure mounting back plate to the junction box using standard junction box screws that come with the junction box.

Note : (i) using any other non-original-manufacturer provided junction box screw may result in safety issue;

(ii) The side of the mounting plate marked "GND" must face out.


CONNECTING THE WIRES (Fig. 2)

6. Connect the fixture's wires to junction box wires as shown in Fig. 2, making sure that all wire connectors (A) are secured. Connect the fixture's ground wire to your outlet box ground wire. After wires are connected, tuck them carefully inside the junction box.
7. Connect the male end connector and female end connector. After the male end connector and female end connector are connected, put them into the junction box.

COMPLETING THE INSTALLATION

8. Secure the fixture to the mounting back plate using the mounting screw (B).

Fig. 2 Wiring



WS-53318 Mounting Back Plate





Fig. 3 Switch



本页仅用于版本控制，请勿印刷！

| 序号 | 变更说明 | 变更人 | 变更日期 |
|----|----------------------------------|-----|------------|
| 1 | 版本控制页增加“短边对折两下”的描述，并修改驱动为 IC 模块。 | 蒋乾 | 12/06/2022 |
| 2 | | | |
| 3 | | | |
| 4 | | | |
| 5 | | | |



料号: 714902118
设计: 蒋乾 11/29/2022

规格: 80 克进口书写纸 A4, 双面印刷, 短边对折两下
审核: 钟俊平 12/06/2022 标准化: 蒋乾 12/07/2022

图号: WS53318-21 B
批准: 李昌勇 12/07/2022