

# 3" Round Flush Mount Trim Adaptor

For 3" Pex™ Round Trims




## Features

- 3" Round extra thin spackle frame for easy mounting.
- Designed to seamlessly flush trims to ceiling.
- Compatible 3" Pex™ Round trims: **ELK3618, ELK3629, ELK3627, ELK3693, ELK3620, ELK3622** Series Only.

## Technical Details

**Construction:** Extra thin spackle frame.


**Installation:** Easy mudding.



**Compatible Trims:** Compatible with 3" Pex Trims.

**Lamp:** Koto™ LED Module.

## Dimensions




## Product Numbers

Item	Description
EL3FMR	3" Round Flush Mount Trim Adapter

# Compatible Products

For use with 3" Pex™ Round Flush Mount Trim Adaptor

## Koto™ LED Module



**Koto™ LED Module**  
ELK07 - ELK09

PRODUCT NUMBER BUILDER			
Koto™ LED Module	Lumens	Color Temperature	Beam Angle
ELK			
07	750 lm	27 2700K	(blank) 38° lens (Standard)
09	950 lm	30 3000K	-S 18° lens
		35 3500K	-N 25° lens
		40 4000K	-W 60° lens
		SD Sunset Dimming (ELK09 Only)	

ACCESSORIES	
	<b>Lens</b>
	<b>Reflectors</b>
EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens
<small>*EP732C, EP733C, EP734C Included</small>	
	<b>Secondary Optics</b>
L45	Hex Louver
L46	Linear Louver
L47	Spread Louver

## 3" Koto™ Dedicated LED ICA Housings




2-Hour Fire Rated 3" ICA Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL39FICA	7 1/2" Height - Sound Rated



3" ICA Maximum Adjustability Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL386ICA	Maximum Adjustability



3" ICA Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL390ICA	
EL390ICA-EM5	Emergency Battery Back-up (90 minutes)



3" ICA Housing  
**Remodel**

CAT NO.	SPECIFICATIONS
EL390RICA	

# Compatible Products

For use with 3" Pex™ Round Flush Mount Trim Adaptor

## Koto™ Architectural LED Light Engine



**Koto™ LED Light Engine**  
ELK19 - ELK21

PRODUCT NUMBER BUILDER			
Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle
ELK			
19	750 - 850 lm	27D 2700K	(blank) 38° lens (Standard)
21	1100 - 1500 lm	30D 3000K	-S 18° lens
		35D 3500K	-N 25° lens
		40D 4000K	-W 60° lens
		SD Sunset Dimming (ELK19 Only)	

### ACCESSORIES




#### Lens

**EP731C** 18° Lens  
**EP732C** 25° Lens  
**EP733C** 38° Lens  
**EP734C** 60° Lens

#### Reflectors

**EP735C** 15°  
**EP736C** 25°  
**EP737C** 38°  
**EP738C** 60°


*EP732C, EP733C, EP734C Included*



#### Secondary Optics


**L45** Hex Louver  
**L46** Linear Louver  
**L47** Spread Louver

## 3" Koto™ Architectural Recessed Housings



**3" High Lumen Maximum Adjustability ICA Housing**  
 1500 lm (18.9W) w/ELK21 Series Module  
 Not for use with ELK19 Series Module  
**New Construction**

CAT NO.	SPECIFICATIONS
E3LK85ICAD	120/277V - 0-10V/Triac/ELV



**3" Shallow Maximum Adjustability ICA Housing**  
 850 lm (14.7W) w/ELK19 Series Module  
 1100 lm (14.7W) w/ELK21 Series Module  
**New Construction**

CAT NO.	SPECIFICATIONS
E3LK76ICA	120V - Triac/ELV
E3LK77ICAD	120/277V - 0-10V/Triac/ELV



**3" Standard ICA Housing**  
 750 lm (10.5W) w/ELK19 Series Module  
 950 lm (10.5W) w/ELK21 Series Module  
**New Construction**

CAT NO.	SPECIFICATIONS
E3LK65ICA	120V - Triac/ELV
E3LK65ICA-EM1	Emergency Battery Back-Up
E3LK66ICAD	120/277V - 0-10V/Triac/ELV
E3LK66ICAD-EM1	Emergency Battery Back-Up



**3" Standard ICA Housing**  
 750 lm (10.5W) w/ELK19 Series Module  
 950 lm (10.5W) w/ELK21 Series Module  
**Remodel**

CAT NO.	SPECIFICATIONS
E3LK65RICA	120V - Triac/ELV



**2-Hour Fire Rated 3" ICA Housing**  
 750 lm (10.5W) w/ELK19 Series Module  
 950 lm (10.5W) w/ELK21 Series Module  
**New Construction**

CAT NO.	SPECIFICATIONS
ELK72FICA	120V - Triac/ELV
ELK73FICAD	120/277V - 0-10V/Triac/ELV

# Compatible Products

For use with 3" Pex™ Round Flush Mount Trim Adaptor

## 3" Pex™ Twist-&-Lock Trims

---



**Round Deep Reflector**

**ELK3618**

Finishes:  
(W, BB, BZ, B, C, H)



**Round Adjustable Gimbal**

**ELK3629**

Finishes:  
(W, BB, BZ, B, C, H)



**Round Adjustable Pinhole**

**ELK3627**

Finishes:  
(B, BB, BZ)



**Round Adjustable Baffle**

**ELK3693**

Finishes:  
(W)



**Round Adj. Slot Aperture**

**ELK3620**

Finishes:  
(W)



**Round Adj. Wall Wash**

**ELK3622**

Finishes:  
(W)



Recommended to be  
used with Maximum  
Adjustability Housing